



IT Channel Solutions

Enabling Business-Critical Continuity for SMB Applications

	Rating (VA / W)	Runtime ¹	Part Number	APC Equivalent	Input Plug ²	Output Plugs	Comms Ports	Net/Tel protection	Intellislot SNMP WEB	Form factor (tower/rack)	Dims and Wgt (HxWxD - mm)	3rd year warranty (Part code)
Liebert PSP 3G Desktop Protection												
	500VA 300W	11 min	PSP500MT3-230U	BK500EI	C14/10A		USB	•	-	Tower	215 x 87 x 251 _3,9 kg	PF1YR-MU-00
	650VA 390W	8 min	PSP650MT3-230U	BK650EI	C14/10A		USB	•	-	Tower	215 x 87 x 251 _3,9 kg	PF1YR-MU-01
Liebert PSA Desktop Protection												
	500VA 300W	12 min	PSA500MT3-230U	BR500I	C14/10A		USB	•	-	Tower	171x95x356 _5,4 kg	PF1YR-MU-01
	650VA 390W	8,5 min	PSA650MT3-230U	BR800I	C14/10A		USB	•	-	Tower	171x95x356 _5,9 kg	PF1YR-MU-01
	1000VA 600W	12 min	PSA1000MT3-230U	BR1000I	C14/10A		USB	•	-	Tower	234x147x360 _9,5 kg	PF1YR-MU-02
	1500VA 900W	10,5 min	PSA1500MT3-230U	BR1500I	C14/10A		USB	•	-	Tower	234x147x360 _11,6 kg	PF1YR-MU-04
Liebert PSI Wiring Closet												
	750VA 675W		PS750RT3-230	SUA750I	C14/10A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶		PF1YR-MU-03
	1000VA 900W	12 min	PS1000RT3-230	SUA1000I	C14/10A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 412 _20 kg	PF1YR-MU-03
	1500VA 1350W	9 min	PS1500RT3-230	SUA1500I	C14/10A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 412 _21 kg	PF1YR-MU-04
	2200VA 1980W	11 min	PS2200RT3-230	SUA2200I	C20/16A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 657 _35 kg	PF1YR-MU-05
	3000VA 2700W	9 min	PS3000RT3-230	SUA3000I	C20/16A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 657 _38 kg	PF1YR-MU-05
Liebert PSI-XR Wiring Closet												
	1000VA 900W	15 min scalable	PS1000RT3-230XR	SUA1000RMI2U	C14/10A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 490,5 _25 kg	PF1YR-MU-03
	1500VA 1350W	13 min scalable	PS1500RT3-230XR	SUA1500RMI2U	C14/10A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 490,5 _28 kg	PF1YR-MU-04
	2200VA 1980W	14 min scalable	PS2200RT3-230XR	SUA2200RMI2U	C20/16A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 700,5 _42 kg	PF1YR-MU-05
	3000VA 2700W	13 min scalable	PS3000RT3-230XR	SUA3000RMI2U	C20/16A		Serial/USB	•	SNMP/Web Card ⁴	Tower_Rack ⁶	2U_88 x 440 x 700,5 _46 kg	PF1YR-MU-05
Liebert GXT2 Wiring Closet												
	700VA 490W	44 min scalable	GXT2-700RT230	N/A	C14/10A		Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	2U_87 x 547 x 430 _22,5 kg	PF1YR-MU-03
	1000VA 700W	25 min scalable	GXT2-1000RT230	SURTD1000XLI/SURTD1000RMLXI	C14/10A		Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	2U_87 x 547 x 430 _22,6 kg	PF1YR-MU-03
	1500VA 1050W	20 min scalable	GXT2-1500RT230	N/A	C14/10A		Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	2U_87 x 547 x 430 _23,2 kg	PF1YR-MU-05
	2000VA 1400W	14 min scalable	GXT2-2000RT230	SURTD2000XLI/SURTD2000RMLXI	C14/10A		Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	2U_87 x 547 x 430 _24,7 kg	PF1YR-MU-05
	3000VA 2100W	16 min scalable	GXT2-3KRT230E	SURTD3000XLI/SURTD3000RMLXI	C20/16A		Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	2U_87 x 618 x 430 _31,9 kg	PF1YR-MU-06
	4500VA 3150W	24 min scalable	GXT2-4500RT230	SURTD5000XLI/SURTD5000RMLXI	Hardwire	Hardwire +	Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	5U_221 x 547 x 430 _67 kg	Please contact us
	6000VA 4200W	17 min scalable	GXT2-6000RT230	SURTD6000XLI/SURTD6000RMLXI	Hardwire	Hardwire +	Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower_Rack ⁶	5U_221 x 547 x 430 _67 kg	Please contact us
	10000VA 7000W	15 min scalable	GXT2-10000R230K	SURTD8000RMLXI	Hardwire	Hardwire +	Serial/USB2 ³	-	SNMP/Web Card ⁵ included	Rack	6U_260 x 660 x 410 _100 kg	Please contact us
	10000VA 7000W	14 min scalable	GXT2-10000T230	SURTD8000XLI	Hardwire	Hardwire	Serial/USB2 ³	-	SNMP/Web Card ⁵	Tower	300 x 800 x 675 _110 kg	Please contact us



Your complimentary use period has ended. Thank you for using PDF Complete.

Click Here to upgrade to Unlimited Pages and Expanded Features

Channel Solutions

Enabling Business-Critical Continuity for SMB Applications



Rating VA	150VA	300VA	450VA	600VA	700VA	850VA	1000VA	1250VA
Runtime	13	5	3	-	-	-	-	-
	14	9	7	4	3	-	-	-
	19	11	9	8	7	6	5	3

MiniTower: Liebert PSPXT
 PSPXT450-230USB
 PSPXT700-230USB
 PSPXT1250-230USB

Rating VA	350VA	500VA	650VA	800VA	900VA	1000VA	1200VA	1500VA
Runtime	7	3	-	-	-	-	-	-
	8.5	4	2	-	-	-	-	-
	26	12	8.5	5	4	3	-	-
	43	16.5	13	9	8	6	4	3

MiniTower: Liebert PSA
 PSA500MT3-230U
 PSA650MT3-230U
 PSA1000MT3-230U
 PSA1500MT3-230U

Rating VA	400VA	800VA	1000VA	1500VA	1800VA	2200VA	2600VA	3000VA
Runtime	18	8.5	5.5	-	-	-	-	-
	31	12	9	-	-	-	-	-
	51	18.5	15	9	7	5	-	-
	62	30	25	13	11	8.5	6.5	5
Extended Runtime	94	48	31.5	-	-	-	-	-
	103	52	42.5	18	-	-	-	-
	108	59	49	27.5	18	15	-	-
	118	66	55	31.5	26.5	17	14.5	12

Rack/MiniTower: Liebert PSI
 PS1000RT3-230XR
 PS1500RT3-230XR
 PS2200RT3-230XR
 PS3000RT3-230XR

Extended batteries for Liebert PSI
 1xPSRT3-24VBXR (with PSI XR 1000VA)
 1xPSRT3-24VBXR (with PSI XR 1500VA)
 1xPSRT3-48VBXR (with PSI XR 2200VA)
 1xPSRT3-48VBXR (with PSI XR 3000VA)

Rating VA	700VA	1000VA	1500VA	2000VA	3000VA	4500VA	6000VA	10000VA
Runtime	17	-	-	-	-	-	-	-
	16	11	-	-	-	-	-	-
	22	12	7	-	-	-	-	-
	22	14	9	6	-	-	-	-
	41	27	16	9	5	-	-	-
	90	61	38	27	17	10	-	-
	84	60	37	26	17	10	7	-
	128	99	73	47	29	17	12	5
	109	84	62	41	26	16	11	5
Extended Runtime	68	-	-	-	-	-	-	-
	64	44	-	-	-	-	-	-
	89	51	28	-	-	-	-	-
	67	42	27	18	-	-	-	-
	164	109	64	38	20	-	-	-
	218	155	10	79	50	31	-	-
	202	153	102	74	49	30	21	-
	312	240	175	110	69	43	29	15
	378	291	231	171	95	61	42	23

Rack/MiniTower: Liebert GXT2

GXT2-700RT230
 GXT2-1000RT230
 GXT2-1500RT230
 GXT2-2000RT230
 GXT2-3KRT230E
 GXT2-4500RT230
 GXT2-6000RT230
 GXT2-10000R230K
 GXT2-10000T-230

Extended batteries for Liebert GXT 2

GXT2-48VBATT (with GXT2 700 VA)
 GXT2-48VBATT (with GXT2 1000 VA)
 GXT2-48VBATT (with GXT2 1500 VA)
 GXT2-48VBATT (with GXT2 2000 VA)
 GXT2-72VBATT (with GXT2 3000 VA)
 GXT2-240VBATT (with GXT2 4500 VA)
 GXT2-240VBATT (with GXT2 6000 VA)
 GXT2-240VBATT (with GXT2 10kVA Rack)
 GXT2-240TBATTCE (with GXT2 10kVA Tower)

Discharge times are rounded and expressed in minutes. For further details please refer to User Manual.

While every precaution has been taken to ensure accuracy and completeness, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Craig Baker, Channel Account Manager
 M: +44(0)7713 504 878
 @: craigw.baker@emerson.com

Daniel McDonald, Channel Account Manager
 M: +44(0)7785 590 297
 @: daniel.mcdonald@emerson.com

Lee Gajic, Channel Account Manager
 M: +44(0)7710 008 936
 @: lee.gajic@emerson.com

Steve Allen, Channel Account Manager
 M: +44(0)7710 189 207
 @: steve.allen@emerson.com

Eben Owen, UK Channel Manager
 M: +44(0)7713 504 875
 @: eben.owen@emerson.com

Available - Not Available



Channel.Liebert.EMEA@emerson.c

Emerson Network Power Fourth Avenue, Globe Park, SL7 1YG
 T: 01628 403200

- 1 50% load
- 2 With C14 input plugs, use input power cord of PC
- 3 Intellislot USB card: USBCARD
- 4 Intellislot SNMP/Web card: IS-WEBRT3
- 5" Intellislot SNMP/Web card: IS-WEBCARD
- 6 Rack mounting kit (included in PSI-XR and optional in GXT2): RAILKITPS3G-AEC