

10G SFP+ Optic

The IEEE 802.3ae committee ratified the 10 Gigabit Ethernet standard and along with the general specification, defined a number of fiber optic interfaces. These standard interfaces attempted to satisfy a number of different objectives including support for MMF and SMF compatibility.

SR SFP+

- 10GBASE-SR transceivers are used in a data center to interconnect two Ethernet switches or to link an end-device (e.g. 10 Gigabit Ethernet servers or NAS device) to an Ethernet switch

LR SFP+

- 10GBASE-LR transceivers are most commonly deployed in inter-building single mode connections

ER SFP+

- 10GBASE-ER transceivers are most commonly deployed in between sites or locations of 40 kilometers

ZR SFP+

- 10GBASE-ZR transceivers are most commonly deployed in between sites or locations of 80 kilometers

COPPER-CU SFP+

- 10GBASE-Copper cables are most commonly deployed in data centers between two devices in the same rack (server to switch or switch to switch)



The SFP+ pluggable interface is an industry standard—Multisource Agreement (MSA) for pluggable 10 Gigabit Ethernet Optics.

Features

SR SFP+

- 10GBASE-SR transceiver support with a link length up to 300 meters over 850 nm multimode fiber, LC Connector

LR SFP+

- 10GBASE-LR transceiver support with a link length up to 10 kilometers over 1310 nm single mode fiber, LC Connector

ER SFP+

- 10GBASE-ER transceiver support with a link length up to 40 kilometers over 1550 nm single mode fiber, LC Connector

ZR SFP+

- 10GBASE-ZR transceiver support with a link length up to 80 kilometers over 1550 nm single mode fiber, LC Connector

COPPER SFP+

- 10GBASE-Copper CU is a direct attached passive twin-ax copper cable with link lengths of 1m to 10m

Technical Specifications

	SR SFP+	LR SFP+	ER SFP+	ZR SFP+	COPPER SFP+
Fiber Type	Multimode (MMF)	Single-mode (SMF)	Single-mode (SMF)	Single-mode (SMF)	N/A
Connector Type	LC	LC	LC	LC	Direct attach
Launch Power min (avg)	-7.3dBm	-8.2dBm	-4.7dB	-4.7dBm	N/A
Receiver Power Range	-1 - -9.9dBm	0.5 - -14.4dBm	-1 - -15.8dBm	-1 - -15.8dBm	N/A
Optical Link Budget	*Depends on fiber type. See below.	7dB	10dB	10dB	N/A
Center Wavelength Range	840 to 860nm	1260 to 1355nm	1530 to 1565nm	1530 to 1565nm	N/A
Distance Range	2m to 300m	2m to 10km	2m-40km	2m-80km	1m-10m
Mean Time Between Failure (MTBF) Hours	4901960	3921568	1399188	1443343	1000000

Note: All Extreme Networks qualified SFP+ plugables meet or exceed the IEEE 802.3ae 10 Gigabit Ethernet specification. The table above shows some SFP+ parameters that may be useful for 10 Gigabit Ethernet deployments

*62.5 μm (160/200 MHz*km) = 1.6 dB (typically 26 meters)

62.5 μm (200 MHz*km) = 1.6 dB (typically 33 meters)

50 μm (400 MHz*km) = 1.7 dB (typically 66 meters)

50 μm (500 MHz*km) = 1.8 dB (typically 82 meters)

50 μm (2000 MHz*km) = 2.6 dB (typically 300 meters)

Physical Specifications

- Dimensions (HxWxD): 0.48x0.54x2.70 in (1.22x1.38x6.86 cm)
- Weight: 0.06 lb (25.1 g) unpackaged, 0.30 lb (135 g) packaged
- Shipping box dimensions (HxWxD): 2.1x6.8x7.7 in (5.4x17.2x19.6 cm)

TECHNICAL SPECIFICATIONS

SFP+ Optics are supported on:

- Summit® X650 Series - XGM2-2xf module
- VIM-10G8X
- Summit X450a/e - XGM2-2bt
- BlackDiamond 8800 series

ENVIRONMENTAL CONDITIONS OPERATIONAL

- Operating Temperature: 0° C to +40° C (32° F to 104° F)
- Operating Humidity: 10% to 93% non-condensing
- Altitude: 0 - 4000 meters (13,000 ft)
- Operational Shock: 30 m/s² (3g), 11ms
- Operational Random Vibration: 5 - 500 Hz @ 1.5 Grms

TRANSPORTATION & STORAGE

- Temperature: -40° C to 70° C (-40° F to 158° F)
- Relative Humidity: 10% to 93%
- Shock: 180 m/s² (18g), 6ms
- Random Vibration: 5 - 20 Hz @ 1.0 ASD w/-3dB/ oct. from 20 - 200 Hz
- Drop: 42" (105cm)

ENVIRONMENTAL STANDARDS

- EN 300 019-2-3 v2.1.2 (2003-04), Stationary Use, Class 3.1e
- EN 300 019-2-2 v2.1.2 (1999-09), Public Transportation, Class 2.3
- EN 300 019-2-1 v2.1.2 (2000-09), Storage, Class 1.2
- RoHS 6 compliant
- China RoHS compliant
- WEEE Compliant

SAFETY COMPLIANCE

North American Safety of ITE

- UL60950:2000 3rd edition of later, Recognized Component
- cUL to CSA 22.2#60950:2000 3rd Ed or later, Recognized Component

European Safety of ITE

- EN60950-1:2001+ all available country deviations
- 2006/95/EC Low Voltage Directive (LVD)

Laser Safety

- EN60825-1:1994, A1:1996, A2:2001
- 21 CFR Subpart J, Class 1 Laser
- CDRH Letter of Approval

EMI/EMC COMPLIANCE

North America EMC for ITE

- FCC CFR 47 Part 15 Class A (U.S.A.)
- ICES-003 Class A (Canada)

European EMC Standards

- EN 55022:2006, Class A
- EN 55024 A2:2003, Class A
- ETSI EN 300 386: v1.4.1 2008-04
- (EMC Telecommunications)
- 2004/108/EC EMC Directive

International EMC Certifications

- CISPR 22:2006 Ed 5.4, Class A (International Emissions)
- CISPR 24 A2:2003, Class A (International Immunity)
 - IEC/EN 61000-4-2:2001 Electrostatic Discharge, 8kV Contact, 15kV Air, Criteria B
 - IEC/EN 61000-4-3:2006 Radiated Immunity 10V/m, 30MHz to 2GHz, Criteria A
 - IEC/EN 61000-4-4:2005 Transient Burst, 1kV, Criteria A
 - IEC/EN 61000-4-5 2005, Surge, 1kV L-L, 2kV L-G, Level 4, Criteria B
 - IEC/EN 61000-4-6:2007 Conducted Immunity, 0.15-80MHz, 10V/m unmod. RMS, Criteria A
 - IEC/EN 61000-4-11:2004 Power Dips & Interruptions, >30%, 25 periods, Criteria A

Note: All SFP+ modules meet the above standards when installed in Extreme Networks equipment.

Ordering Information

PART NUMBER	NAME	DESCRIPTION
10301	10GBASE-SR SFP+	10GBASE-SR SFP+, 850nm, LC Connector, transmission length of up to 300m on MMF
10302	10GBASE-LR SFP+	10GBASE-LR SFP+, 1310nm, LC Connector, transmission length of up to 10km on SMF
10309	10GBASE-ER SFP+	10GBASE-ER SFP+, 1550nm, LC Connector, transmission length of up to 40km on SMF
10310	10GBASE-ZR SFP+	10GBASE-ZR SFP+, 1550nm, LC Connector, transmission length of up to 80km on SMF
10304	10G SFP+ CU Cable 1m	10G SFP+ CU direct attached passive twin-ax copper cable with link lengths of 1m
10305	10G SFP+ CU Cable 3m	10G SFP+ CU direct attached passive twin-ax copper cable with link lengths of 3m
10306	10G SFP+ CU Cable 5m	10G SFP+ CU direct attached passive twin-ax copper cable with link lengths of 5m
10307	10G SFP+ CU Cable 10m	10G SFP+ CU direct attached passive twin-ax copper cable with link lengths of 10m



<http://www.extremenetworks.com/contact> / Phone +1-408-579-2800

©2014 Extreme Networks, Inc. All rights reserved. Extreme Networks and the Extreme Networks logo are trademarks or registered trademarks of Extreme Networks, Inc. in the United States and/or other countries. All other names are the property of their respective owners. For additional information on Extreme Networks Trademarks please see <http://www.extremenetworks.com/about-extreme/trademarks.aspx>. Specifications and product availability are subject to change without notice. 1535-0414