



# IBM System Storage DS3500 Express

*Affordable performance and flexibility without sacrificing scalability, efficiencies or ease of use*

---

## Highlights

- 6 Gigabits per second (Gbps) Serial Attached SCSI (SAS) systems deliver midrange performance and scalability at entry-level prices
  - Energy saving implementations for cost savings
  - Management expertise built into an intuitive and powerful storage management software
  - Mixed host interfaces for Direct Access Storage (DAS) and Storage Area Network (SAN) tiering can reduce overall operation and acquisition costs
  - Full Disk Encryption (FDE) with local key management provides relentless data security.
- 

IBM has combined best-of-breed development with leading 6 Gbps host interface and drive technology in the IBM System Storage DS3500 Express. With its simple, efficient and flexible approach to storage, the DS3500 is a cost-effective, fully integrated complement to System x servers, BladeCenter and Power Systems. Offering substantial improvements at a price that will fit most budgets, the DS3500 delivers superior price to performance ratios, functionality, scalability and ease of use for the entry-level storage user.

DS3500 Express is designed to offer:

- Scalability to midrange performance and features starting at entry-level prices
- Efficiencies to help reduce annual energy expenditures and environmental footprint
- Simplicity that does not sacrifice control with the perfect combination of robustness and ease of use.

## 6 Gbps SAS – midrange performance and scalability at entry-level prices

6 Gbps SAS is the enterprise version of SAS building on the solid foundation of 3 Gbps SAS technology. 6 Gbps SAS offers increased performance, scalability and reliability enhancements to support the ever-increasing reliance on information while delivering outstanding value that organisations are demanding.



Delivering solid input/output operations per second (IOPS) and throughput, the DS3500's controllers continue IBM's tradition of balanced and sustainable performance. The DS3500 can effectively double the performance of the current DS3000 series of storage systems in both throughput and IOPS. With up to 4,000 MegaBytes per second (MBps) and 40,000 IOPs in sustained drive reads, the DS3500 is equally adept at delivering throughput to bandwidth-intensive applications and IOPs to databases and Exchange.

And with support up to 96 drives, scalability has doubled from the previous-generation systems. By dynamically adding drive enclosures (up to seven EXP3512, four EXP3524 expansion enclosures or a mix of the two) with virtually no downtime, you can quickly and seamlessly respond to growing capacity demands. This scalability also improves overall system performance by distributing the server's input/output (I/O) requests across a greater number of drives.

### **Energy saving implementations for cost savings today and tomorrow**

With rising energy expenses and IT space constraints, efforts to reduce power consumption in a small IT footprint have quickly come to the forefront as hot-button IT issues for many organisations. To respond to these challenges, IBM has made great strides in energy efficient implementations with the DS3500 by introducing new power saving features that do not impact performance, scalability, or functionality.

Smaller form-factor 2.5-inch SAS drives, one of multiple drives supported by the DS3500, provide up to three times the IOPs per watt in power consumption than 3.5-inch drives and enable twice as many drives to reside in the same 2U of rack space. 2.5-inch drives also deliver impressive IOPs performance in a small form-factor (SFF) with minimal impact on IBM power consumption or heat dissipation.



Energy-efficient power supplies ensure just that – energy efficiency. By efficiently converting AC power from electric utilities into DC power used by the storage system, the DS3500 power supplies ensure that overall annual expenditures are lower than other less efficient implementations. And with low heat dissipation, the DS3500 can become a key component of an overall energy-saving and green solution.

The DS3500 continues in the tradition of superior disk utilisation that enables IBM customers to achieve maximum return on investment (ROI) on their storage investment. The DS series can deliver almost up to two times the disk utilisation of leading competitors allowing organisations to achieve maximum performance with fewer drives and less energy consumption.

### **Intuitive and simple storage management that doesn't sacrifice control**

Blending the ease of use and intuitive nature of the DS3000 Storage Manager as well as the robustness and functionality previously only available on the DS5000 and DS4000, the new DS Storage Manager for the DS3500 delivers a simple storage management interface that provides great control while maintaining its simplicity.

The DS3500 now offers dynamic and other high-functionality capabilities, which were previously only available via the command line interface (CLI) with the earlier generation of the DS3000 Storage Manager allowing administrators to make changes to their configurations as and when needed with no downtime. The new DS Storage Manager graphical user interface (GUI) was designed for both experienced full-time storage administrators who want complete control over their storage configuration as well as part-time system administrators who desire an intuitive interface that ensures optimal storage utilisation with the least amount of effort.

### **A singular DS Storage Manager with remote mirroring**

The DS3500's DS Storage Manager is the same management software offered with the DS5000 and DS4000 series. Now, any of these storage systems can be viewed and managed from a single interface. This allows for consolidated management of these various storage systems as well as a reduced learning curve. The DS3500 also supports enhanced remote mirroring over Fibre Channel (FC) host ports, which is also compatible with the DS5000 and DS4000 series. This allows for low-cost backup and recovery with a DS5000 and DS4000 at a production site and a DS3500 at the secondary site.



### **Mixed host interfaces support enables DAS and SAN tiering**

Administrators can now benefit from tiered DAS and SAN implementations with multi-protocol host connectivity. The DS3500 supports intermixing four 1 Gbps SCSI over IP (iSCSI) or four 8 Gbps FC host ports with its native 6 Gbps SAS interfaces. This flexible and multi-purpose dual protocol approach allows organisations to implement a single storage system to support all of their shared storage requirements, thereby maximising productivity, reliability and cost.

Multiprotocol host connectivity offers a number of advantages for the system administrator:

- Low cost high speed SAS delivers the best value and performance for DAS implementations
- Data centres with existing iSCSI or FC SAN infrastructures can cost-effectively implement these additional host interfaces as required. iSCSI is ideal for low cost implementations for secondary servers and FC is well positioned for high performance and robust deployments.

### **Relentless data security with local key management and FDE**

In the lifecycle of a hard drive, it will at some point be out of the user's control either through theft, off-site service, repair or disposal. The DS3500 combines local key management and drive-level encryption for comprehensive data security that ensures that data is protected throughout the life of the drive without sacrificing storage system performance or ease of use.

- FDE provides data security at the most basic level, the hard drive. FDE protects against many exposures and vulnerabilities all at once. This drive-level encryption ensures data security in the event of a drive loss, theft or retirement. The FDE engine performs encryption without a performance penalty, which allows organisations to achieve the highest levels of data security while retaining optimal performance
- Fully integrated into the DS Storage Manager as a premium feature upgrade, the DS3500's local key management provides the necessary management and protection of self-encrypting disk (SED) drives by utilising a single authorisation scheme, or lock key, which can be set and applied to all SED drives within a DS3500. The DS Storage Manager maintains and controls the key linkage and communications with the SED drives, secures user-selected logical drive groups and initiates the instant secure erase feature for customers desiring even more peace of mind when servicing, decommissioning, or repurposing drives. With local encryption services, FDE key management is transparent to day-to-day storage administration, making SED drives as easy to manage as traditional drives.

### **Tiered storage with high performance and nearline (NL) SAS drives and SAS SED drive intermix**

The DS3500, similar to the DS3000, DS4000 and DS5000 storage systems, can cost-effectively support an organisation's complete range of data capacity requirements – from NL static data to highly utilised applications – through support for mixed drive types within a single storage system. The DS3500 accomplishes this with the additional support for NL SAS drives, SAS SED drives and 2.5-inch SAS drives to its traditional 3.5-in drives. NL SAS drives are also the clear

replacement of SATA drives. Competitively priced to Serial Advanced Technology Attachment (SATA) drives, NL SAS drives significantly outperform SATA and do so with greater reliability at a comparable price.

Now, organisations can meet even more granular and specific requirements for their application needs, whether these requirements include security for data at rest, leading performance and/or energy efficiency. This exciting capability maximises storage density and provides a more efficient utilisation of enclosures when implementing a tiered storage solution.

### **Storage and Application Monitors now available with IBM Tivoli Storage**

IBM Tivoli Storage Productivity Centre for Disk Midrange Edition V4.1 is designed to provide storage device configuration, performance monitoring and management of SAN attached devices from a single console. In addition, it includes performance monitoring capabilities for the DS3500.

Tivoli Storage Productivity Centre for Disk Midrange Edition V4.1:

- Offers continuous real-time monitoring and fault identification to help improve SAN availability
- Provides performance reporting across multiple arrays from a single console
- Helps monitor metrics such as throughput, I/O and data rates, as well as cache utilisation
- Receives timely alerts that can enable event action based on your policies when thresholds are exceeded
- Helps to improve storage ROI by aiding to keep SANs reliably and dependably operational
- Can reduce storage administration costs by helping simplify the management of complex SANs.

## Key applications/workloads

- **Consolidation/virtualisation** Balanced performance, low-cost consolidation and unparalleled configuration flexibility make the DS3500 ideally suited for smaller consolidation and virtualisation implementations where an individual storage system supports diverse workloads and application requirements
- **Departmental and remote sites** Simple enough for a part-time administrator and at a price that won't break a corporation's budget to support its departmental and remote sites, the DS3500 brings the right amount of performance, simplicity and functionality that will allow these locations to be self-sufficient
- **Transactional workloads** Efficient IOPS make the DS3500 well suited for transactional workloads (online transactional processing (OLTP), databases, email) that are the core of every company's critical applications
- **Data warehousing** Solid throughput and 6 Gbps SAS and 8 Gbps FC interfaces make the DS3500 well suited for data warehousing environments where an individual storage system must process large amounts of data
- **Business-critical applications** With bullet-proof reliability, support for SED drives and exceptional uptime, the DS3500 supports business-critical applications where data must be protected and available when needed
- **Secondary storage** With support for Redundant Array of Independent Disk (RAID 6) and NL SAS drives, the DS3500 can store large amounts of data cost-effectively with confidence that it's fully protected
- **Clustered topologies** SAS based shared storage and FC or iSCSI SAN implementations are ideal for clustering solutions such as MSCS and Oracle RAC when transitioning from a DAS implementation
- **Streaming video** Large-block I/O applications, such as world-class broadcasting, rich media storage networks, content creation, modelling and publishing, will benefit from the additional bandwidth that the DS3500 series offers
- **Data mining** With FC and SAS host connectivity, companies can accelerate and scale simulation, visualisation, modelling and rendering applications easily to accelerate large dataset I/O rates, as well as cost-effectively scale and share information across the organisation for high-level collaboration
- **Backup and restore** With the ability to mirror data between storage systems over FC, the DS3500 can support short backup windows and recovery time for high productivity
- **Campus area replication** When replicating data across a high-speed FC SAN, data can be mirrored synchronously, ensuring that remote sites have the exact same data as the local site at all times.

---

**IBM System Storage DS3500 Express at a glance**

---

**Characteristics**

Model	1746A2S / 1746A2D and 1746A4S / 1746A4D
RAID controller	Dual Active, hot-swappable controllers
Cache	1 GB cache per controller with 2 GB upgrade (battery-backed)
Host interface	Three options: -Four or eight 6 Gbps SAS ports -Eight 8 Gbps FC ports and four 6 Gbps SAS ports -Eight 1 Gbps iSCSI ports and four 6 Gbps SAS ports
Drive interface	Two 6 Gb SAS drive ports
Supported drives	6 Gbps SAS 3.5" drives: -300 GB 15k revolutions per minute (rpm), 450 GB 15k rpm, 600 GB 15k rpm -1 TB 7.2k rpm NL, 2 TB 7.2k rpm NL -600 GB 15k rpm SED 6 Gbps SAS 2.5" drives: -146 GB 15k rpm -300 GB 10k rpm -500 GB 7.2k rpm NL -300 GB 10k rpm SED
RAID levels	0, 1, 3, 5, 6, 10
Storage partitions	Support for up to 64 storage partitions (levels: 4 standard with upgrades to 8, 16, 32, 64)
Maximum drives supported	-Up to 96 drives – high performance SAS drives, NL SAS drives and SED SAS drives -EXP3512 (2U 12 3.5-in drives) and EXP3524 (2U 24 2.5-in drive) enclosures, which can be intermixed behind a DS3500 enclosure
Fans and power supplies	Dual redundant, hot-swappable
Rack support	2U, 19-inch, industry-standard rack
Management software	IBM System Storage DS Storage Manager
SAN support	Supported IBM FC switches and directors, as well as Internet Protocol (IP) switches
Warranty	Three year parts and labour warranty, nine to five, next business day, upgradeable to around-the-clock with six-hour response

**IBM System Storage DS3500 Express at a glance**

**Physical Characteristics**

Dimensions	DS3512: Height: 3.39 in./86.16 mm, Width: 18.99 in./482.47 mm, Depth: 21.72 in./551.60 mm DS3524: Height: 3.47 in./88.07 mm, Width: 18.98 in./482.10 mm, Depth: 19.60 in./497.93 mm		
Supported systems	For a list of currently supported servers, operating systems, host bus adapters (HBAs), clustering applications and SAN switches and directors, refer to the DS3500 Express Interoperability Matrix available at <a href="http://ibm.com/systems/support/storage/config/ssic/">ibm.com/systems/support/storage/config/ssic/</a> For availability dates, configuration options and attachment capabilities, refer to: <a href="http://ibm.com/systems/storage/disk">ibm.com/systems/storage/disk</a>		
Model	Model description	Interface	Model includes
1746-A2E/EXP3512 1746-A4E/EXP3524	Drive Enclosure	6 Gb SAS	ESM-imbedded
<b>Relative Humidity (no condensation)</b>	EXP3512/EXP3524 Drive Enclosure		
Operating range	20 to 80 percent		
Storage range	10 to 90 percent		
Maximum dew point	79°F (26°C)		
Maximum gradient	10 percent per hour		
<b>Altitude ranges</b>			
Operating	100 ft (30.5 m) below sea level to 10,000 ft (3048 m) above sea level		
Storage	100 ft (30.5 m) below sea level to 10,000 ft (3048 m) above sea level		
Transit	100 ft (30.5 m) below sea level to 40,000 ft (12,000 m) above sea level		
The tabulated power and heat dissipation values are the maximum measured operating power.			
<b>Acoustic noise</b>	EXP3512/EXP3524 Drive Enclosure		
Sound power	6.5 bels		
Sound pressure	65 dBA		
<b>Power input</b>	EXP3512/EXP3524 Drive Enclosure		
Nominal voltage range	90 V ac to 264 V ac		
Frequency range	50 to 60 Hz		
Max operating current	3.90 A at 115 V ac 2.06 A at 230 V ac		

## For more information

To learn more about the [IBM System Storage DS3500 Express](#), please contact your IBM marketing representative or IBM Business Partner, or visit:  
[ibm.com/systems/storage/disk/ds3500](http://ibm.com/systems/storage/disk/ds3500)

IBM offers tailored financing solutions to credit-qualified clients that can be customised to address your specific IT needs from great rates to flexible payment plans and loans. Our asset management services include certified used equipment, online asset management, buyback, asset disposal and disk overwrite. For more information on IBM Global Financing, visit: [ibm.com/financing/uk](http://ibm.com/financing/uk)



---

### IBM United Kingdom Limited

PO Box 41  
North Harbour  
Portsmouth  
Hampshire  
PO6 3AU  
United Kingdom

### IBM Ireland Limited

Oldbrook House  
24-32 Pembroke Road  
Dublin 4

IBM Ireland Limited registered in Ireland under company number 16226.

The IBM home page can be found at [ibm.com](http://ibm.com)

IBM, the IBM logo, [ibm.com](http://ibm.com), BladeCenter, DS4000, Power Systems, System Storage, System Storage DS, System x and Tivoli are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries.

A current list of IBM trademarks is available on the Web at 'Copyright and trademark information' at [ibm.com/legal/copytrade.shtml](http://ibm.com/legal/copytrade.shtml).

Other company, product and service names may be trademarks, or service marks of others.

References in this publication to IBM products, programs or services do not imply that IBM intends to make these available in all countries in which IBM operates.

Any reference to an IBM product, program or service is not intended to imply that only IBM products, programs or services may be used. Any functionally equivalent product, program or service may be used instead.

IBM hardware products are manufactured from new parts, or new and used parts. In some cases, the hardware product may not be new and may have been previously installed. Regardless, IBM warranty terms apply.

This publication is for general guidance only.

Information is subject to change without notice. Please contact your local IBM sales office or reseller for latest information on IBM products and services.

IBM does not provide legal, accounting or audit advice or represent or warrant that its products or services ensure compliance with laws. Clients are responsible for compliance with applicable securities laws and regulations, including national laws and regulations.

Photographs may show design models.

© Copyright IBM Corporation 2010  
All Rights Reserved.



Please Recycle