



IBM System x3650 M3 server models include Intel Xeon 5600 series processors and some preloaded models with SAP Discovery software

Table of contents

2 Overview	11 Product number
3 Key prerequisites	11 Publications
3 Planned availability date	12 Technical information
3 Description	27 Pricing
10 Product positioning	29 Announcement countries

At a glance



Power, scalability, control, and serviceability for dynamic web-serving and on demand business applications:

- Ultrathin, high-availability, rack-optimized, 2U platform
- 2 GB, 4 GB, 8 GB, or 16 GB of high-speed DDR-3 SDRAM Registered DIMM memory; 18 DIMM slots that support up to 192 GB maximum memory with 16 GB optional DIMMs, or support up to 48 GB of DDR3 SDRAM Unbuffered DIMM memory via 12 DIMM slots
- Support for up to sixteen 2.5-inch hot-swap SAS or hot-swap SATA HDDs or SSDs
- Four PCI-Express x8 Gen 2 slots:
 - Two x8 - full length, full height
 - One x8 - half length, full height
 - One x8 - low profile
- 460-watt ac, 675-watt ac, 675-watt dc, and 675-watt high-efficiency ac, auto-ranging power supplies (model dependent)
- Integrated systems management processor
- Integrated dual Gigabit Ethernet ports (standard) for high I/O capacity, plus two additional GbE ports (option) with failover capability
- One serial port (16550A-compatible), four USB ports (front and rear), and two video ports (front and rear)

This 2U-high, rack-optimized server features superior power, optimized performance, and leadership virtualization and systems management for business-critical workloads built on IBM® X-Architecture®.

Optimized for energy efficiency and performance

New, innovative, energy-smart design with powerful high-performance processors, a large capacity of high-performing DDR3 memory, and a no-compromise feature set ideal for most general business applications:

- Powerful Intel® quad- and six-core processors
- New energy-efficient design incorporating 460 W and 675 W high-efficiency power supplies, six cooling fans (three banks of counter-rotating dual fans), altimeter (barometric pressure sensor), and energy-efficient planar components to help lower operational costs
- Highly functional chipset optimized for better application computing for general business workloads
- Eighteen DIMM slots that enable you to deploy up to 192 GB of DDR3 SDRAM Registered DIMM memory, with 4 GB memory standard, or support up to 48 GB of DDR3 SDRAM Unbuffered DIMM memory via 12 DIMM slots
- Standard SAS/SATA HDDs or SSDs with RAID support on hot-swap models
- Support for up to sixteen hot-swap SAS/SATA HDDs or SSDs
- Integrated Dual Gigabit Ethernet ports (standard) for high I/O capacity, and two additional GbE ports (optional) with failover capability
- Support for Embedded VMware ESXi 4.1 hypervisor (connector on an internal SAS riser card activated with optional 2 GB USB key)
- Four PCI-Express x8 high-performance Gen 2 I/O slots that help provide greater network performance with long-term investment protection (four PCIe x8 convertible to two x16 PCIe or four PCI-X 64-bit slots)
- NEBS 1/ETSI equivalent compliance for both ac and dc power supply (model dependent)
- Compliance with 80PLUS and ENERGY STAR standards (model dependent)

Manage with efficiency

High availability, manageability, and serviceability features help diagnose problems quickly, even from remote locations:

- IBM Systems Director Active Energy Manager™ for advanced datacenter power notification and management to help achieve lower heat output and reduced cooling needs
- Snoop filters to boost processor performance
- Integrated SAS controller supporting up to sixteen 2.5-inch hot-swap HDD bays (four or eight bays standard, four-bay kits that upgrade from four to eight bays or eight-bay kits that upgrade from eight to sixteen bays optional) with five RAID alternatives, helping to safeguard your data with either the standard RAID controller at no additional cost or an optional RAID controller for enhanced support.
- Memory mirroring, configurable using Unified Extensible Firmware Interface (UEFI) setup
- Integrated Management Module (IMM) systems management processor
- Monitoring and control of operating status and key server components
- Predictive Failure Analysis® (PFA) on selected components that warns of problems before they occur
- Fast and easy servicing through innovative light path diagnostics, improved onboard diagnostics, and LED diagnostic panel

Ultimate fault tolerant protection

- Hot-swap, redundant fans with calibrated vectored cooling to keep components cool, and simplified fan replacement
- Optional hot-swap, redundant power supplies to help reduce down time
- IBM Director and web support
- Three-year, Customer Replaceable Unit (CRU) and on-site labor¹, limited warranty²; optional warranty service upgrades available

IBM is releasing models of this product that come preloaded with SAP Discovery System V4. The SAP Discovery System is an out-of-the-box, fully configured and preintegrated service-oriented architecture (SOA) platform enabler for SAP development environments. The models that include the preinstalled copy of SAP software do not include a license to use such SAP software. You are not licensed to use the copy of SAP software contained in the IBM system until you have purchased or licensed the use of the SAP software from SAP or its authorized distributors. Usage of the SAP software is subject to the applicable SAP end-user license supplement. Your purchase of the IBM hardware system does not include a license to use the SAP software or to use any other SAP software. SAP is under no obligation to license the preloaded SAP software to you. Please contact your responsible SAP representative to obtain the appropriate license rights to use the SAP software. SAP Discovery Server is preinstalled on specific models of this product as a convenience only; IBM makes no representation or warranty with respect to SAP software and grants no license to use any preinstalled SAP software.

¹ You may be asked certain diagnostic questions before a technician is sent.

² For information on IBM's Statement of Limited Warranty, contact your IBM representative or reseller. Copies are available upon request.

³ GHz and MHz denote the internal and/or external clock speed of the microprocessor only, not application performance. Many factors affect application performance.

Note: The Microsoft® Windows® Preinstallation Environment software contains a security feature that will cause an end-user customer's system to reboot without prior notification to the end-user customer after 24 hours of continuous use of the Microsoft Windows Preinstallation Environment. During routine usage of ServerGuide™, which does not usually require usage of the Microsoft Windows Preinstallation Environment software for such an extended time period, this condition should not occur.

Key prerequisites

- Monitor, USB keyboard, and USB mouse

Note: PS/2-style keyboard and mouse are not supported.

Planned availability date

March 15, 2011 -- All models except:

- IBM System x3650 M3 (7945J6x): April 8, 2011

Description

System x3650 M3 server

The System x3650 M3 server features Intel Xeon® multicore processors that support internal processing speeds of up to 3.46 GHz³ (six-core) or 3.60 GHz (four-core) and processing operations to memory up to 1333 MHz.

High-performance server subsystems

The System x3650 M3 server expands the new server line by adding a higher level of processor power. This high-throughput, two-way multicore network server offers excellent performance and scalability when you add memory and a second processor. It incorporates powerful Xeon processors with up to 12 MB L3 cache. The advanced transfer L3 cache is integrated onto the processor and runs at the same clock speed. The advanced transfer cache is a result of a "backside bus" 256 bits wide. It features a quad-wide cache line that can transfer four 64-bit cache line segments at one time to deliver full-speed capability. The cache is eight-way set associative.

Two Intel Xeon processor connectors are standard on the system board to support installation of a second processor. High-speed PC3 DDR3 Advanced Memory Feature DIMMs run at 1333 MHz DRAM clock speed and offer maximum 10667 MB/s bandwidth, processor-to-memory subsystem performance. The x3650 M3 server uses the Intel 5600 chipset with Chipkill™ technology to maximize throughput from processors, to memory, to the 32-bit and 64-bit PCI buses.

Standard System x3650 M3 configurations

SEO number	Processor	Memory	GT/s	HDD interface	HDD	Other
794512x	1.60 GHz Cache: 4 MB	4 GB	4.8	SAS/SATA	2.5-in	Open bay hot-swap 1 x 460W
794522x	2.13 GHz Cache: 8 MB	4 GB	4.8	SAS/SATA	2.5-in	Open bay hot-swap 1 x 460W
794532x	2.26 GHz Cache: 8 MB	4 GB	4.8	SAS/SATA	2.5-in	Open bay hot-swap 1 x 460W
7945D4x	2.40 GHz Cache: 12 MB	4 GB	5.86	SAS/SATA	2.5-in	Open bay hot-swap 1 x 460W
7945H4x	2.26 GHz Cache: 12 MB	4 GB	5.86	SAS/SATA M5015	2.5-in	Open bay hot-swap 1 x 460W
794552x	2.40 GHz Cache: 12 MB	4 GB	5.86	SAS/SATA M5014	2.5-in	Open bay hot-swap 1 x 460W
794554x	2x2.40 GHz Cache: 12 MB	8 GB	5.86	SAS/SATA M5014	2.5-in	Open bay hot-swap 2 x 675W HE
794562x	2.53 GHz Cache: 12 MB	4 GB	5.86	SAS/SATA M5014	2.5-in	Open bay hot-swap 1 x 460W
7945J4x	2.66 GHz Cache: 12 MB	4 GB	6.4	SAS/SATA M5015	2.5-in	Open bay hot-swap 1 x 675W
7945J6x	2x2.66 GHz Cache: 12 MB	24 GB	6.4	SAS/SATA M5015 Multiburner	2.5-in	1x500 GB 7x300 GB hot-swap SAP Disc 2 x 675W HE
7945L4x	2.80 GHz Cache: 12 MB	4 GB	6.4	SAS/SATA M5015	2.5-in	Open bay hot-swap 1 x 675W
794572x	3.06 GHz Cache: 12 MB	4 GB	6.4	SAS/SATA M5015	2.5-in	Open bay hot-swap 1 x 675W HE
794582x	3.46 GHz Cache: 12 MB	4 GB	6.4	SAS/SATA M5015	2.5-in	Open bay hot-swap 1 x 675W HE

Note: The model "x" designation is geography dependent and is spelled out explicitly in the [Product number](#) section.

Additional features

- Up to twelve-core processing achieved with a second processor of equal speed and processor type
- System board containing 18 DIMM connectors supporting 2 GB, 4 GB, 8 GB, and 16 GB DDR3 PC3-10600 SDRAM ECC RDIMMs with:
 - DDR3 memory for improved performance
 - Up to 192 GB of system memory using 16 GB optional DIMMs
 - Up to 48 GB of system memory using 4 GB DDR3 PC3-10600 SDRAM ECC UDIMM memory
 - Two DIMMs per channel at 1333 MHz supported on single-rank and dual-rank RDIMMs and UDIMMs for L5640, E5645, E5649, and X5600 series 1333 MHz processors
- High-speed, wide-bandwidth PCI-Express or PCI/PCI-X bus slots
- On standard models, either four or eight 2.5-inch bays to support optional SAS HDDs and one bay to support an optical drive (optical standard in some models)
- Dual Broadcom 5709 chip that supports dual Gigabit (10/100/1000) Ethernet ports, which speed network communications to LAN clients

The System x3650 M3 server offers solid system throughput from processor, to memory, to bus, to disk-intensive I/O. These features, combined with multicore capability, make the x3650 M3 server an excellent choice for a stand-alone or clustered general-business application, file, and print server.

High-availability and serviceability features

The System x3650 M3 server subsystem delivers excellent reliability and serviceability features:

- Support for light path diagnostics with viewable drop-down panel, Wake on LAN®, and PXE
- Up to six hot-swap fans (three pairs)
- Up to sixteen 2.5-inch HS HDDs with optional upgrade kit levels
- Chipkill memory that basically distributes information covered by error correction coding across separate memory chips; if any of the chips fail, the data can in many cases still be reconstructed from the remaining chips, and the system can continue running
- ECC L3 cache processors to help improve data integrity and help reduce down time
- Predictive Failure Analysis (PFA) on processors, HDD options, memory, voltage regulator modules (VRMs), power supply, and fans (when Remote Supervisor Adapter is installed), to help alert the system administrator of imminent component failure
- Worldwide voltage-sensing, 460-watt ac, 675-watt ac, 675-watt high-efficiency ac, and 675-watt dc hot-plug power supply
- Optional 460-watt ac, 675-watt ac, 675-watt high-efficiency ac, and 675-watt dc hot-swap power supply upgrade
- Optional Virtual Media Key to enable the remote presence and blue-screen capture features
- Integrated Management Module systems management processor that supports:
 - Automatic server restart (ASR)
 - Fan monitoring and control
 - Power supply monitoring
 - Temperature monitoring
 - Voltage monitoring
 - Power on/off, reset sequencing

- LED controls (onboard diagnostics support with light path LED)
- Remote power control
- Local firmware update
- Error logging
- Information LED panel for visual indications of system well-being
- Onboard diagnostics with an LED map to locate a failing component, helping reduce down time and service costs
- Support for virtual floppy (with optional Virtual Media Key), which enables a user to easily direct a remote host to boot, and use standard instructions stored anywhere on the network
- Easily accessible system board, adapter cards, processor, and memory
- CPU failure recovery in configurations, which:
 - Forces the failed processor offline
 - Reboots the server automatically
 - Generates alerts
 - Continues operations with the working processor

Expandability and growth

The System x3650 M3 server packs a lot of function and storage capacity into a 2U 19-inch rack-drawer package, yet it is amazingly easy to upgrade and service. Functions such as SVGA video, SAS, and full-duplex 10/100/1000 Mbps Ethernet are integrated on the system board. Features include:

- Rack-drawer models designed for 19-inch-wide by 28-inch-deep industry-standard rack enclosures, such as the NetBAY42 SR
- Four PCI/PCI-Express adapter card slots available (2 x PCI-Express slots may be replaced by a riser card option to get two PCI-X slots)
- System board optional upgrades (PCI slot not required)
 - IBM Virtual Media Key
- Support for up to 16000 GB of internal data storage, using sixteen 1 TB NL SAS/ NL SATA HDDs

Systems management

Integrated Management Module (IMM)

The System x3650 M3 includes an integrated Management Module that provides industry-standard Intelligent Platform Management Interface (IPMI) 2.0-compliant systems management. The IMM comes standard, and shares one of the two onboard Ethernet ports for access. The IMM can be accessed via software that is compatible with IPMI 2.0 (xCAT, for example). The IMM is implemented using industry-leading OSA firmware and applications in conjunction with the Integrated Management Module.

Features and benefits:

- Monitoring:
 - System voltages
 - Battery voltage
 - System temperatures
 - Fan speed control
 - Fan tachometer monitor
 - Good Power signal monitor
 - System ID and planar version detection
 - System power and reset control

- NMI detection (system interrupts)
- SMI detection and generation (system interrupts)
- Serial port text console redirection
- System LED control (power, HDD, activity, alerts, and heartbeat)
- An embedded web server that gives you remote control from any standard web browser. No additional software is required on the remote administrator's workstation.
- For users who are accustomed to a command-line interface (CLI), the ability of the administrator to use the CLI from a Telnet session to perform some of the functions that can be performed from the web server.
- Secure Socket Layer (SSL) and Lightweight Directory Access Protocol (LDAP).
- Built-in LAN and serial connectivity that supports virtually any network infrastructure.
- Multiple alerting functions to warn systems administrators of potential problems through email, IPMI PEs, and SNMP.

With video compression now built into the adapter hardware, the adapter allows the greater screen sizes and refresh rates that are becoming common in the marketplace. This feature helps enable the user to display server activities from power-on to full operation remotely with remote user interaction at virtually any time.

IBM Virtual Media Key

The optional Virtual Media Key delivers advanced control and monitoring features to manage your IBM System x3650 M3 server at virtually any time, from virtually any place. The key can be added to the server through a connector on the planar. This key enables easy console redirection with text and graphics, and keyboard and mouse (operating system must support USB) support over the system management LAN connections.

IBM Director

The System x3650 M3 server also features IBM Director, a powerful, highly integrated, systems-management software solution built on industry standards and designed for ease of use. Exploit your existing enterprise or workgroup-management environments, and use rich security to access and manage physically dispersed IT assets more efficiently over the Internet. It can help reduce costs through potentially:

- Reduced down time
- Increased productivity of IT personnel and end users
- Reduced service and support costs

IT administrators can view the hardware configuration of remote systems in detail, and monitor the usage and performance of critical components such as processors, HDDs, and memory.

IBM Director includes a portfolio of integrated server tools that work with the systems management monitoring functions. Typical functions and monitoring capabilities can include:

- PFA-enabled critical hardware components
- Temperature
- Voltage
- Fan speed
- Light path diagnostics

IT administrators have comprehensive, virtual on-site control of System x servers with the ability to remotely:

- Access the server, often regardless of its status
- Inventory and display detailed system and component information
- View server bootup during POST
- Browse and delete logs of events and errors
- Reset or power cycle the server
- Monitor and set thresholds on server health including:
 - Operating system load
 - POST time-out
 - Voltage
 - Temperature
- Set proactive alerts for critical server events including PFA on:
 - Processors
 - Memory
 - HDDs
 - Voltage regulator modules (VRMs)
 - Power supplies
 - Fans
- Define automated actions, such as:
 - Send email or page to an administrator
 - Execute a command or program
 - Pop up an error message to the IBM Director console
- Flash UEFI
- Monitor and graph the use of server resources, such as:
 - Memory
 - Processor
 - HDDs
- Identify potential performance bottlenecks and react to prevent down time

IBM Director Agent integrates into leading workgroup and enterprise systems management environments via upward integration modules (available from IBM and third parties). Advanced management capabilities built into System x® servers are available through:

- Tivoli® Enterprise and Tivoli NetView®
- Computer Associates Unicenter TNG
- HP OpenView
- Microsoft SMS
- BMC Patrol
- NetIQ

IBM Active Energy Manager

IBM Active Energy Manager offers direct monitoring of power consumption and thermal load of your server through IBM Director. You can monitor power consumption to track utilization of energy resources. IBM Active Energy Manager is a leading solution on the market providing users with the combination of intelligence and features needed to effectively monitor power consumption in the datacenter. Active Energy Manager, an extension to IBM Director systems management software, allows clients to "meter" actual power usage and trend data for any single physical system or group of systems. Developed by IBM Research, Active Energy Manager utilizes IBM-developed monitoring circuitry to help identify how much actual power is being used and the temperature of the system. The software is available across IBM's new System x servers, as well as its BladeCenter® line of

systems. With Active Energy Manager, the user is able to understand the actual power draw.

With the addition of the optional IBM Virtual Media Key, the IT administrator achieves comprehensive, virtual on-site control of System x servers through the ability to remotely:

- Access the server, in many cases regardless of the status
- Inventory and display detailed system and component information
- View server bootup during POST
- Browse and delete logs of events and errors
- Reset or power cycle the server
- Run diagnostics, SCSI, and RAID setup during POST
- Monitor thresholds on server health, including:
 - Operating system load
 - POST time-out
 - Voltage
 - Temperature
- Set proactive alerts for critical server events, including PFA on:
 - Processors
 - Memory
 - Fans
 - HDDs
 - Voltage regulator modules (VRMs)
 - Power supplies
- Define automated actions, such as:
 - Send an email or a page to an administrator
 - Execute a command or program
 - Pop-up an error message to the director console
- Manage flash UEFI
- Monitor and graph the utilization of server resources, such as:
 - Memory
 - Processor
 - HDDs
- Identify potential performance bottlenecks and react to prevent down time
- Monitor, manage, and configure RAID subsystems without taking them off line

Advanced Configuration and Power Interface (ACPI)

ACPI is an open industry specification that defines a flexible and extensible hardware interface for the system board. Software designers use this specification to integrate power management features throughout a computer system, including hardware, the operating system, and application software. This integration enables Microsoft Windows to determine which applications are active, and handle all of the power management resources for computer subsystems and peripherals.

World-class support tools and programs

The System x3650 M3 server tools and programs can make ownership a positive experience. From the start, IBM programs help you purchase servers, get them running, and keep them running. IBM can help your company maintain ownership of technology leadership network servers.

- The server purchase includes a three-year, customer replaceable unit (CRU) and on-site service, limited warranty; optional warranty service upgrades are available.
- The ServerProven® program lets you confidently configure your server with various devices and operating systems. This web-based program provides compatibility information from actual testing of the System x3650 server with various adapters and devices.
- Electronic support on the web offers additional support in an easy-to-use format.

<http://www.ibm.com/servers/eserver/serverproven/compat/us/>

Accessibility by people with disabilities

A U.S. Section 508 Voluntary Product Accessibility Template (VPAT) containing details on accessibility compliance can be requested at

http://www.ibm.com/able/product_accessibility/index.html

Product positioning

The System x3650 M3 servers are a part of the System x rack-optimized server line. These two-socket servers deliver Intel Xeon multicore power and excellent server function in an ultrathin, rack-optimized, 2U footprint.

Optimized for speed

The System x3650 M3 server offers new levels of fast Intel Xeon multicore processors with up to 6.4 GT/s and lower power for datacenter environments and collaboration applications. This server is uniquely optimized for better application computing with a highly functional chipset and eighteen DIMM slots for a maximum of 192 GB of DDR-3 SDRAM Registered DIMM memory.

Innovation comes standard

- Application efficiency increases with snoop filters that free up cache and improve processor performance.
- Supercharged TOE optimizes system performance by offloading protocol processing.
- A drop-down light path diagnostics panel improves in-rack manageability and allows easy problem identification.

Ultimate fault-tolerant protection

- A memory mirroring feature enables you to increase memory reliability.
- A SAS controller with RAID-0, -1, and -1E on hot-swap SAS models helps safeguard your data at no additional cost.

Target applications

- Database
- Email collaboration
- File/print
- Virtualization
- Linux® clustering
- Scientific and technical computing

These powerful servers also meet traditional enterprise network server requirements, but with an added benefit of requiring less space.

Product number

Note: EMEA are GAV models.

Description	MT	Mod	Part number
IBM System x3650 M3	7945	12G	794512G
	7945	22G	794522G
	7945	32G	794532G
	7945	D4G	7945D4G
	7945	H4G	7945H4G
	7945	52G	794552G
	7945	54G	794554G
	7945	62G	794562G
	7945	J4G	7945J4G
	7945	J6G	7945J6G
	7945	L4G	7945L4G
	7945	72G	794572G
	7945	82G	794582G

Note: SAP Discovery system v4 preload SAP Business All-in one is included with the 7945J6G.

Starting Point models:

Description	Part number
System x 3650 M3 Starting Point	7945-FT3
System x 3650 M3 Starting Point	7945-FT4

The following are new unique option part numbers for System x3650 M3 server.

Option part number	Description
81Y6557	IBM 675W High Efficiency Redundant AC Power Supply
81Y6558	IBM 465W Redundant AC Power Supply
81Y6537	Intel Xeon Processor E5645 6C 2.40GHz 12MB Cache 1333MHz 80w
81Y6538	Intel Xeon Processor E5603 4C 1.60GHz 4MB Cache 1066MHz 80w
81Y6539	Intel Xeon Processor E5606 4C 2.13GHz 8MB Cache 1066MHz 80w
81Y6540	Intel Xeon Processor E5607 4C 2.26GHz 8MB Cache 1066MHz 80w
81Y6541	Intel Xeon Processor X5647 4C 2.93GHz 12MB Cache 1066MHz 130w
81Y6542	Intel Xeon Processor E5649 6C 2.53GHz 12MB Cache 1333MHz 80w
81Y6543	Intel Xeon Processor X5672 4C 3.20GHz 12MB Cache 1333MHz 95w
81Y6544	Intel Xeon Processor X5675 6C 3.06GHz 12MB Cache 1333MHz 95w
81Y6545	Intel Xeon Processor X5687 4C 3.60GHz 12MB Cache 1333MHz 130w
81Y6546	Intel Xeon Processor X5690 6C 3.46GHz 12MB Cache 1333MHz 130w

Publications

The following CD-ROM is shipped with the x3650 M3 server:

- IBM Director systems management software is included.

Note: Software versions, features, and functions shipped with these systems may change as new releases become available or discontinued at any time.

The *System x3650 M3 Server Installation and User's Guide* and *Problem Determination and Service Guide*, in U.S. English versions, are available from

<http://www-304.ibm.com/jct01004c/systems/support/>

Select "Product Support," "System x," then "Product family," and then click "Publications lookup."

IBM Publications Center Portal

<http://www.ibm.com/shop/publications/order>

The Publications Center is a worldwide central repository for IBM product publications and marketing material with a catalog of 70,000 items. Extensive search facilities are provided, as well as payment options, via credit card. A large number of publications are available online in various file formats, which can currently be downloaded free of charge.

Displayable softcopy publications

The product books are offered in displayable softcopy form. All books are included. The displayable manuals are part of the basic machine-readable material. The files are shipped on DVD-ROM. Terms and conditions for use of the machine-readable files are shipped with the files.

Services

Global Technology Services

IBM services include business consulting, outsourcing, hosting services, applications, and other technology management.

These services help you learn about, plan, install, manage, or optimize your IT infrastructure to be an On Demand Business. They can help you integrate your high-speed networks, storage systems, application servers, wireless protocols, and an array of platforms, middleware, and communications software for IBM and many non-IBM offerings. IBM is your one-stop shop for IT support needs.

For details on available services, contact your IBM representative or visit

<http://www.ibm.com/services/>

For details on available IBM Business Continuity and Recovery Services, contact your IBM representative or visit

<http://www.ibm.com/services/continuity>

For details on education offerings related to specific products, visit

<http://www.ibm.com/services/learning/index.html>

Select your country, and then select the product as the category.

Technical information

Specified operating environment

Physical specifications

System x3650 M3:

7945J6x

Processor	Xeon 6C X5650 (95w)
Internal speed	2.66 GHz
External speed	6.4 GTS
Number standard	2
Maximum	2

L3 cache (full-speed)	12 MB
Memory	24 GB ECC
RDIMMs	6 x 4 GB
DIMM sockets	18
Capacity (4)	192 GB
Video	SVGA
Memory	16 MB
SATA controller	SAS/SATA
Channels	4
Connector internal	1
HDD (5)	
Total bays	9 (standard)
5.25 slim	1
3.5-in tape	0
Hot-swap (3.5-in)	0
Hot-swap (2.5-in)	8 standard (1 x 500 GB and 7 x 300 GB)
Internal capacity	9.6 TB (with upgrade)
Bays available	0
5.25 slim	0
3.5-in tape	0
Hot-swap (3.5-in)	0
Hot-swap (2.5-in)	0
Total PCI slots	4
PCI_E (x8) (6)	4
System management	Standard
Ethernet controller	Two 1 Gb
Optical drive (SATA)	Multiburner
Power supply	675 W HE
Number standard	2
Maximum	2
Hot-swap	Yes
Redundant power	Yes
Auto restart	Yes

System x3650 M3:

	794512x	794522x
Processor	Xeon 4C E5603 (80 W)	Xeon 4C E5606 (80 W)
Internal speed	1.60 GHZ	2.13 GHZ
External speed	4.8 GT/s	4.8 GT/s
Number standard	1	1
Maximum	2	2
L3 cache (full-speed)	4 MB	8 MB
Memory	4 GB ECC	4 GB ECC
RDIMMs	1 x 4 GB	1 x 4 GB
DIMM sockets	18	18
Capacity (4)	192 GB	192 GB
Video	SVGA	SVGA
Memory	16 MB	16 MB
SATA controller	SAS/SATA	SAS/SATA
Channels	4	4
Connector internal	4	4
HDD (5)		
Total bays	5 (standard)	9 (standard)
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	4 standard	8 standard
Internal capacity	9.6 TB (with upgrade)	9.6 TB (with upgrade)
Bays available	5	9
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	4	8
Total PCI slots	4	4
PCI_E (x8) (6)	4	4
System management	Standard	Standard
Ethernet controller	Two 1 Gb	Two 1 Gb
Optical drive (SATA)	Optional	Optional
Power supply	460 W	460 W
Number standard	1	1
Maximum	2	2

Hot-swap	Yes	Yes
Redundant power	Optional	Optional
Auto restart	Yes	Yes

System x3650 M3:

	794532x	7945D4x
Processor	Xeon 4C E5607 (80w)	Xeon 4C E5620 (80w)
Internal speed	2.26 GHZ	2.40 GHZ
External speed	4.8 GTS	5.86 GTS
Number standard	1	1
Maximum	2	2
L3 cache (full-speed)	8 MB	12 MB
Memory	4 GB ECC	4 GB ECC
RDIMMs	1 x 4 GB	1 x 4 GB
DIMM sockets	18	18
Capacity (4)	192 GB	192 GB
Video	SVGA	SVGA
Memory	16 MB	16 MB
SATA controller	SAS/SATA	SAS/SATA
Channels	4	4
Connector internal	4	4
HDD (5)		
Total bays	9 (standard)	9 (standard)
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8 standard	8 standard
Internal capacity	9.6 TB (with upgrade)	9.6 TB (with upgrade)
Bays available	9	9
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8	8
Total PCI slots	4	4
PCI_E (x8) (6)	4	4
System management	Standard	Standard
Ethernet controller	Two 1Gb	Two 1Gb
Optical drive (SATA)	Optional	Optional
Power supply	460 w	460 w
Number standard	1	1
Maximum	2	2
Hot-swap	Yes	Yes
Redundant power	Optional	Optional
Auto restart	Yes	Yes

System x3650 M3:

	7945H4x	794552x
Processor	Xeon 6C L5640 (60w)	Xeon 6C E5645 (80w)
Internal speed	2.26 GHZ	2.40 GHZ
External speed	5.86 GTS	5.86 GTS
Number standard	1	1
Maximum	2	2
L3 cache (full-speed)	12 MB	12 MB
Memory	4 GB ECC	4 GB ECC
RDIMMs	1 x 4 GB	1 x 4 GB
DIMM sockets	18	18
Capacity (4)	192 GB	192 GB
Video	SVGA	SVGA
Memory	16 MB	16 MB
SATA controller	SAS/SATA	SAS/SATA
Channels	4	4
Connector internal	4	4
HDD (5)		
Total bays	9 (standard)	9 (standard)
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8 standard	8 standard
Internal capacity	9.6 TB (with upgrade)	9.6 TB (with upgrade)

Bays available	9	9
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8	8
Total PCI slots	4	4
PCI_E (x8) (6)	4	4
System management	Standard	Standard
Ethernet controller	Two 1Gb	Two 1Gb
Optical drive (SATA)	Optional	Optional
Power supply	460 w	460 w
Number standard	1	1
Maximum	2	2
Hot-swap	Yes	Yes
Redundant power	Optional	Optional
Auto restart	Yes	Yes

System x3650 M3:

	794554x	794562x
Processor	Xeon 6C E5645 (80w)	Xeon 6C E5649 (80w)
Internal speed	2.40 GHZ	2.53 GHZ
External speed	5.86 GTS	6.4 GTS
Number standard	2	1
Maximum	2	2
L3 cache (full-speed)	12 MB	12 MB
Memory	8 GB ECC	4 GB ECC
RDIMMs	2 x 4 GB	1 x 4 GB
DIMM sockets	18	18
Capacity (4)	192 GB	192 GB
Video	SVGA	SVGA
Memory	16 MB	16 MB
SATA controller	SAS/SATA	SAS/SATA
Channels	4	4
Connector internal	4	4
HDD (5)		
Total bays	9 (standard)	9 (standard)
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8 standard	8 standard
Internal capacity	9.6 TB (with upgrade)	9.6 TB (with upgrade)
Bays available	9	9
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8	8
Total PCI slots	4	4
PCI_E (x8) (6)	4	4
System management	Standard	Standard
Ethernet controller	Two 1Gb	Two 1Gb
Optical drive (SATA)	Optional	Optional
Power supply	675 w HE	460 w
Number standard	2	1
Maximum	2	2
Hot-swap	Yes	Yes
Redundant power	Standard	Optional
Auto restart	Yes	Yes

System x3650 M3:

	7945J4x
Processor	Xeon 6C X5650 (95w)
Internal speed	2.66 GHZ
External speed	6.4 GTS
Number standard	1
Maximum	2
L3 cache (full-speed)	12 MB
Memory	4 GB ECC
RDIMMs	1 x 4 GB
DIMM sockets	18

Capacity (4)	192 GB
Video	SVGA
Memory	16 MB
SATA controller	SAS/SATA
Channels	4
Connector internal	4
HDD (5)	
Total bays	9 (standard)
5.25 slim	1
3.5-in tape	0
Hot-swap (3.5-in)	0
Hot-swap (2.5-in)	8 standard
Internal capacity	9.6 TB (with upgrade)
Bays available	9
5.25 slim	1
3.5-in tape	0
Hot-swap (3.5-in)	0
Hot-swap (2.5-in)	8
Total PCI slots	4
PCI_E (x8) (6)	4
System management	Standard
Ethernet controller	Two 1Gb
Optical drive (SATA)	Optional
Power supply	675 w
Number standard	1
Maximum	2
Hot-swap	Yes
Redundant power	Optional
Auto restart	Yes

System x3650 M3:

	7945L4x	794572x
Processor	Xeon 6C X5660 (95w)	Xeon 6C X5675 (95w)
Internal speed	2.80 GHz	3.06 GHz
External speed	6.4 GTS	6.4 GTS
Number standard	1	1
Maximum	2	2
L3 cache (full-speed)	12 MB	12 MB
Memory	4 GB ECC	4 GB ECC
RDIMMs	1 x 4 GB	1 x 4 GB
DIMM sockets	18	18
Capacity (4)	192 GB	192 GB
Video	SVGA	SVGA
Memory	16 MB	16 MB
SATA controller	SAS/SATA	SAS/SATA
Channels	4	4
Connector internal	4	4
HDD (5)		
Total bays	9 (standard)	9 (standard)
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8 standard	8 standard
Internal capacity	9.6 TB (with upgrade)	9.6 TB (with upgrade)
Bays available	9	9
5.25 slim	1	1
3.5-in tape	0	0
Hot-swap (3.5-in)	0	0
Hot-swap (2.5-in)	8	8
Total PCI slots	4	4
PCI_E (x8) (6)	4	4
System management	Standard	Standard
Ethernet controller	Two 1Gb	Two 1Gb
Optical drive (SATA)	Optional	Optional
Power supply	675 w	675 w HE
Number standard	1	1
Maximum	2	2
Hot-swap	Yes	Yes
Redundant power	Optional	Optional
Auto restart	Yes	Yes

System x3650 M3:

7945-82x

Processor	Xeon 6C x5690 (130w)
Internal speed	3.46 GHz
External speed	6.4 GTS
Number standard	1
Maximum	2
L3 cache (full-speed)	12 MB
Memory	4 GB ECC
RDIMMs	1 x 4 GB
DIMM sockets	18
Capacity (4)	192 GB
Video	SVGA
Memory	16 MB
SATA controller	SAS/SATA
Channels	4
Connector internal	4
HDD (5)	
Total bays	9 (standard)
5.25 slim	1
3.5-in tape	0
Hot-swap (3.5-in)	0
Hot-swap (2.5-in)	8 standard
Internal capacity	9.6 TB (with upgrade kit)
Bays available	9
5.25 slim	1
3.5-in tape	0
Hot-swap (3.5-in)	0
Hot-swap (2.5-in)	8
Total PCI slots	4
PCI_E (x8) (6)	4
System management	Standard
Ethernet controller	Two 1Gb
Optical drive (SATA)	Optional
Power supply	675 W HE
Number standard	1
Maximum	2
Hot-swap	Yes
Redundant power	Optional
Auto restart	Yes

⁴ Maximum of 192 GB by using 12 x 16 GB optional DIMMs.

⁵ The standard system can hold four or eight 2.5-inch HS HDDs. Maximum capacities are based on installation of sixteen 600 GB SAS HDDs with one or two optional 8-bay HDD expansion options.

Note: For the latest information on supported HDD options, refer to the *Sales Manual* or visit

<http://www.ibm.com/servers/eserver/serverproven/compat/us/>

⁶ PCI_E is the standard feature for PCI or you may replace it with the PCI Riser Card PCI-X Option for PCI/PCI-X 133 MHz/100 MHz 64-bit, or 66/33 MHz/32 bit slots.

Video subsystem

- SVGA compatible video controller (Matrox G200eV).
- Integrated on Integrated Management Module (IMM).
- Integrated on planar and connected to the PCI bus.
- DDR2-250MHz SDRAM video memory controller.
- Video memory is not expandable.
- One DVI (Digital Video Interface) is not used.
- Avocent Digital Video Compression (with Virtual Media Key option).

Supported video mode capabilities for the SVGA PCI controller with a 200 MHz memory clock:

Microsoft windows 2008 or windows 2003 (32- and 64-bit) and Linux (all distributions)

Resolution	Colors	Refresh rate (Hz)
640 x 480 x 8	256	60, 72, 75, 85, 90, 100, 120, 160, 200
640 x 480 x 16	64K	60, 72, 75, 85, 90, 100, 120, 160, 200
640 x 480 x 32	16M	60, 72, 75, 85, 90, 100, 120, 160, 200
800 x 600 x 8	256	60, 70, 72, 75, 85, 90, 100, 120, 160, 200
800 x 600 x 16	64K	60, 70, 72, 75, 85, 90, 100, 120, 160, 200
800 x 600 x 32	16M	60, 70, 72, 75, 85, 90, 100, 120, 160
1024 x 768 x 8	256	60, 70, 72, 75, 85, 90, 100, 120, 140, 150, 160, 200
1024 x 768 x 16	64K	60, 70, 72, 75, 85, 90, 100, 120, 140, 150, 160, 200
1024 x 768 x 32	16M	60, 70, 72, 75, 85, 90, 100
1280 x 1024 x 8	256	60, 72, 75
1280 x 1024 x 16	64K	60, 72, 75
1280 x 1024 x 32	16M	60, 72, 75

Note: Some modes are not supported by all monitors.

Dimensions

2U Rack Drawer

- width: 443.6 mm (17.5 in.)
- Depth: 698.0 mm (27.5 in.)
- Height: 85.4 mm (3.36 in.)

Rack:

- weight: (minimum configuration) 21.1 kg (46.5 lb)
- weight: (maximum configuration) 25.0 kg (55 lb)

Electrical

Models with 675 W power supplies:

- 100 to 127 (nominal) V ac; 50 Hz or 60 Hz; 7.8 A
- 200 to 240 (nominal) V ac; 50 Hz or 60 Hz; 3.8 A
- Input kilovolt-amperes (kVA) (approximately):
 - Minimum configuration: 0.12 kVA
 - Maximum configuration: 0.78 kVA

Models with 460 W power supplies:

- 100 to 127 (nominal) V ac; 50 Hz or 60 Hz; 5.3 A
- 200 to 240 (nominal) V ac; 50 Hz or 60 Hz; 2.6 A
 - Minimum configuration: 0.12 kVA
 - Maximum configuration: 0.53 kVA
- Btu output:
 - Minimum configuration: 307 Btu/hr (90 watts)
 - Maximum configuration: 2260 Btu/hr (780 watts)
- Noise level (horizontal position): 6.5 bels (operating)
- Noise level (horizontal position): 6.3 bels (idle)

Note: The noise emission level stated is the declared (upper limit) sound power level, in bels, for a random sample of machines. All measurements are made in accordance with ISO 7779 and reported in conformance with ISO 9296.

System x3650 M3 server are intended for use as rack-drawer servers and are tested and designed to operate in a horizontal position.

- Russia/GOST ME01, IEC-60950-1, GOST R 51318.22-99, GOST R 51318.24-99, GOST R 51317.3.2-2006, GOST R 51317.3.3-99
- IEC 60950-1 (CB Certificate and CB Test Report)
- CE Mark (EN55022 Class A, EN60950-1, EN55024, EN61000-3-2, EN61000-3-3)
- CISPR 22, Class A
- TUV-GS (EN60950-1 /IEC60950-1,EK1-ITB2000)

Operating environment

Air temperature:

- Server on: 10 degrees C to 35 degrees C (50.0 degrees F to 95.0 degrees F); altitude: 0 to 914.4 m (3,000ft). Decrease system temperature by 0.75 degrees C for every 1,000-foot increase in altitude.
- Server off: 5 degrees C to 45 degrees C (41.0 degrees F to 113 degrees F)
- Shipment: -40 degrees C to +60 degrees C (-40 degrees F to 140 degrees F)

Humidity:

- Server on: 20% to 80%, maximum dew point 21 degrees C, maximum rate of change 5 C/hr
- Server off: 8% to 80%, maximum dew point 27 degrees C

Hardware requirements

For attended installation of an operating system, this server requires a compatible:

- Keyboard
- Mouse
- HDD
- Display

Unattended or remote installation may be performed without requiring some or all of these components. Review your unattended software installation program information for specific hardware configuration requirements.

For service, the server requires a compatible:

- Keyboard
- Mouse
- HDD
- Display

When having the unit serviced, plan to have these components attached to your server either directly or indirectly via a console switch.

Software requirements

The following software products have been tested by IBM and software publishers in the latest available versions, and where appropriate, are or will soon be certified by the publisher to be compatible with the System x3650 M3.

Operating systems

- Microsoft
 - Microsoft Windows Server 2008 R2

- Microsoft Windows Server 2008, Datacenter x64 Edition
- Microsoft Windows Server 2008, Enterprise x64 Edition
- Microsoft Windows Server 2008, Standard x64 Edition
- Microsoft Windows Server 2008, Web x64 Edition
- Windows Small Business Server 2008 Premium Edition
- Windows Small Business Server 2008 Standard Edition
- Linux
 - SUSE Linux Enterprise Server 11 for AMD64/EM64T
 - SUSE Linux Enterprise Server 11 with Xen for AMD64/EM64T
- VMware
 - VMware ESX 4.1
 - VMware ESXi 4.1

Note: For information on additional support, certification, version information, or network operating systems, visit

<http://www-03.ibm.com/servers/eserver/serverproven/compat/us/>

IBM makes no representation or warranty regarding third-party products, including those designated as ServerProven.

Compatibility

The System x3650 M3 server systems contain licensed system programs that include set configuration, set features, and test programs. System UEFI is loaded from a "flash" EEPROM into system memory. This UEFI provides instructions and interfaces designed to support the standard features of the x3650 M3 and to maintain compatibility with many current software programs.

For detailed information about IBM and non-IBM devices, adapters, software, and network operating systems supported with xSeries® servers, visit

<http://www-03.ibm.com/servers/eserver/serverproven/compat/us/>

Contact your IBM representative or IBM Business Partner, or refer to the *IBM Sales Manual* for information on the compatibility of hardware and software for System x servers. The *Sales Manual* is updated periodically as new features and options are announced that support these servers.

Limitations

- The System x3650 M3 server contains a single, configurable serial port. It can be configured to be operating-system-controlled, service-processor-controlled, or shared between the two. You can set the configuration by UEFI configuration. The default configuration from the factory is in the shared position. In the shared position, the service processor controls the port until the operating system is running, then the operating system takes control. The service processor can regain control of the port for user-configured dial-out situations or if the operating system is not available, but operating system control cannot be reestablished without resetting the server.
- To ensure proper air flow for cooling, the System x3650 M3 server requires a rack with a perforated door, such as the NetBAY42 SR or NetBAY25 SR. An alternative is to remove the front door of rack cabinets where the door panel is of solid construction.
- Microprocessor upgrades must be of the same type and clock speed. Mixing microprocessors of different speeds or cache size is not supported.

Note: Refer to the [Software requirements](#) section for operating system limitations.

Planning information

Customer responsibilities

The System x3650 M3 server is designated as customer setup. Customer setup instructions are shipped with each system.

Configuration information

Integrated RAID-1 configuration

There are two manufacturing instructions (MI) available to allow the user to set up a RAID-1 configuration.

The two instructions are:

- Integrated Mirroring - Two HDDs required via Instruction 01R1356
- Integrated Mirroring with HotSpare - Three HDDs required via Instruction 01R1357

Cabling

Simple-swap non-RAID configuration contains cables supporting up to four simple-swap non-RAID SATA drives. It does not contain any backplane.

Rack installations

System x3650 M3 server 2U rack-drawer models are designed to be installed in a 19-inch rack cabinet designed for 28-inch deep devices, such as the NetBAY42U ER and NetBAY42U SR. Installation into some of the older Netfinity® racks (9306900, 9306910, 9306200) requires a rack extension kit.

If a System x3650 M3 is mounted in a non-IBM rack, the rack must satisfy the following specifications:

- The rack must meet EIA-310-D standards for mounting flanges and hole locations.
- The front to rear distance of the mounting flanges must be between 698.5 - 762 mm (27.5 in. - 30 in.).
- The thickness of the mounting flanges must be between 1.9 - 3.3 mm.
- The mounting flanges must have either 7.1-mm (.28 in.) diameter holes or 9.6-mm (.38 in.) square holes on the standard EIA hole spacing.
- The rack must have a minimum depth of 70 mm (2.76 in.) between the front mounting flange and inside of the front door for appropriate cooling.
- The rack must have a minimum depth of 157 mm (6.2 in.) between the rear mounting flange and inside of the rear door to install the server and make space for cable management.
- The minimum side-to-side clearance in the rack between the front and rear mounting flanges must be 467 mm (18.2 in.) to accommodate the width of the server and the slide mounting brackets.
- The minimum side-to-side clearance in the rack between each door and the mounting flanges must be 484 mm (19.1 in.) to accommodate the slide mounting brackets.
- The rack must include perforated front and rear doors and must not prevent the flow of cool air into or out of the rack.
- The weight-handling capacity of the rack must be able to support the maximum rack configuration, including all servers, external cables, and PDUs.
- The rack must provide proper stabilization so that the rack does not become unstable when servers are pulled out for service.

Processor upgrade options

59Y4018 Intel Xeon Processor L5630 4C 2.13GHz 12M Cache 1066MHz 40w

59Y4020	Intel	Xeon Processor	E5620	4C	2.40GHZ	12M	Cache	1066MHZ	80w
59Y4021	Intel	Xeon Processor	E5630	4C	2.53GHZ	12M	Cache	1066MHZ	80w
59Y4022	Intel	Xeon Processor	E5640	4C	2.66GHZ	12M	Cache	1066MHZ	80w
81Y6538	Intel	Xeon Processor	E5603	4C	1.60GHZ	4MB	Cache	1066MHZ	80w
81Y6539	Intel	Xeon Processor	E5606	4C	2.13GHZ	8MB	Cache	1066MHZ	80w
81Y6540	Intel	Xeon Processor	E5607	4C	2.26GHZ	8MB	Cache	1066MHZ	80w
59Y4023	Intel	Xeon Processor	X5650	6C	2.66GHZ	12M	Cache	1333MHZ	95w
59Y4024	Intel	Xeon Processor	X5660	6C	2.80GHZ	12M	Cache	1333MHZ	95w
59Y4025	Intel	Xeon Processor	X5667	4C	3.06GHZ	12MB	Cache	1333MHZ	95w
59Y4026	Intel	Xeon Processor	X5670	6C	2.93GHZ	12MB	Cache	1333MHZ	95w
59Y4027	Intel	Xeon Processor	X5677	4C	3.46GHZ	12M	Cache	1333MHZ	130w
59Y4028	Intel	Xeon Processor	X5680	6C	3.33GHZ	12M	Cache	1333MHZ	130w
81Y6537	Intel	Xeon Processor	E5645	6C	2.40GHZ	12MB	Cache	1333MHZ	80w
81Y6541	Intel	Xeon Processor	X5647	4C	2.93GHZ	12MB	Cache	1066MHZ	130w
81Y6542	Intel	Xeon Processor	E5649	6C	2.53GHZ	12MB	Cache	1333MHZ	80w
81Y6543	Intel	Xeon Processor	X5672	4C	3.20GHZ	12MB	Cache	1333MHZ	95w
81Y6544	Intel	Xeon Processor	X5675	6C	3.06GHZ	12MB	Cache	1333MHZ	95w
81Y6545	Intel	Xeon Processor	X5687	4C	3.60GHZ	12MB	Cache	1333MHZ	130w
81Y6546	Intel	Xeon Processor	X5690	6C	3.46GHZ	12MB	Cache	1333MHZ	130w
59Y4017	Intel	Xeon Processor	L5609	4C	1.86GHZ	12M	Cache	1066MHZ	40w
59Y4019	Intel	Xeon Processor	L5640	6C	2.26GHZ	12M	Cache	1333MHZ	60w
59Y4015	Intel	Xeon Processor	E5503	2C	2.0GHZ	4M	Cache	800MHZ	80w
59Y4016	Intel	Xeon Processor	E5507	4C	2.26GHZ	4M	Cache	800MHZ	80w

Supported memory options

The following memory options are supported:

44T1592	2GB	1Rx8	2Gbit	PC3-10600R-999	LP	RDIMM			
44T1599	4GB	2Rx8	2Gbit	PC3-10600R-999	LP	RDIMM			
46C7449	8GB	PC3-10600	CL9	ECC	DDR3	1333MHZ	Chipkill	LP	RDIMM
46C7483	16GB	4Rx4	2Gbit	PC3-8500	DDR3-1066	LP	RDIMM		
49Y1392	2GB	2Rx8	1Gbit	PC3L-10600R	LP	RDIMM	1.35V	Capable	
49Y1394	4GB	2Rx4	1Gbit	PC3L-10600R	LP	RDIMM	1.35V	Capable	
49Y1397	8GB	2Rx4	2Gbit	PC3L-10600R	LP	RDIMM	1.35V	Capable	
49Y1398	8GB	2Rx4	2Gbit	PC3L-8500R	LP	RDIMM	1.35V	Capable	
49Y1400	16GB	(2Gb, 4Rx4, 1.35V)	PC3L-8500R	LP	RDIMM				
49Y1405	2GB	(2Gb, 1Rx8, 1.35V)	PC3L-10600R	ECC	LP	RDIMM			
49Y1406	4GB	(2Gb, 1Rx4, 1.35V)	PC3L-10600R	ECC	LP	RDIMM			
49Y1407	4GB	(2Gb, 2Rx8, 1.35V)	PC3L-10600R	ECC	LP	RDIMM			
49Y1433	2GB	(1x2GB, 2Rx8, 1.5V)	PC3-10600	CL9	ECC	DDR3	1333MHZ	LP	RDIMM
49Y1434	2GB	(1x2GB, 1Rx4, 1.5V)	PC3-10600	CL9	ECC	DDR3	1333MHZ	LP	RDIMM
49Y1435	4GB	(1x4GB, 2Rx4, 1.5V)	PC3-10600	CL9	ECC	DDR3	1333MHZ	LP	RDIMM
49Y1436	8GB	(1x8GB, 2Rx4, 1.5V)	PC3-10600	CL9	ECC	DDR3	1333MHZ	LP	RDIMM
44T1569	2GB	(1x2GB)	2Rx8	1Gbit	PC3-10600	DDR3-1333	LP	UDIMM	
49Y1404	4GB	(2Gb, 2Rx8, 1.35V)	PC3L-10600E	LP	UDIMM				

Power considerations

The System x3650 M3 server includes a standard 460-watt or 675-watt hot-swap power supply (model dependent). Either power supply supplies sufficient power to run the server.

Cable orders

Two 10/100/1000 Mbps, full-duplex Ethernet PCI controllers, standard with the System x3650 M3 server, are connected directly to an independent RJ-45 connector. The RJ-45 connector provides a 10BASE-T, 100BASE-TX, and 1000BASE-TX interface for connecting twisted-pair cable to the Ethernet network. Cabling is not included with the server. To connect the Ethernet controller to a repeater or switch, use an unshielded twisted pair (UTP) cable with RJ-45 connectors at both ends. For 100/1000 Mbps operation, Category 5 cabling must be used. For 10 Mbps operation, Category 3, or better, cabling must be used.

There are no additional cabling requirements, other than for system power, keyboard, mouse, and monitor connections.

Installability

The System x3650 M3 server requires about 20 minutes for installation. Installation includes unpacking, setting up, and powering on the system. Additional time is required to install an operating system, additional adapters, or features.

Packaging

Product	Package description	Boxes
System x3650 M3	System unit carton	1
	Contents:	
	System unit Rack kit	
System x3650 M3	System unit carton	1
	Contents:	
	Important Notices Flyer Rack Installation Instructions CD - Documentation CD - Director	

The System x3650 M3 server system is shipped as a single package. Other items are in zipped bags or boxes.

Security, auditability, and control

Security and auditability features include:

- Power-on and privileged access password functions control access to the data and server setup program on the server.
- Set unattended boot mode allows the system keyboard to be locked to all entries except the password and at the same time allows other computers on the network to access the system disk drive.
- Selectable boot sequence can be used to prevent unauthorized installation of software or removal of data from the diskette drive.

The servers are intended to be installed in a rack and secured in a rack. It is a customer's responsibility to ensure that the server is secure to prevent sensitive data from being removed.

The customer is responsible for evaluation, selection, and implementation of security features, administrative procedures, and appropriate controls in application systems and communications facilities.

Global Technology Services

Contact your IBM representative for the list of selected services available in your country, either as standard or customized offerings, for the efficient installation, implementation, and/or integration of this product.

IBM Electronic Services

IBM has transformed its delivery of hardware and software support services to help you achieve higher system availability. Electronic Services is a web-enabled solution that offers an exclusive, no-additional-charge enhancement to the service and support available for IBM servers. These services are designed to provide the opportunity for greater system availability with faster problem resolution and preemptive monitoring. Electronic Services comprises two separate, but complementary, elements: Electronic Services news page and Electronic Services Agent.

The Electronic Services news page is a single Internet entry point that replaces the multiple entry points traditionally used to access IBM Internet services and support. The news page enables you to gain easier access to IBM resources for assistance in resolving technical problems.

The Electronic Service Agent™ is no-additional-charge software that resides on your server. It monitors events and transmits system inventory information to IBM on a periodic, client-defined timetable. The Electronic Service Agent automatically reports hardware problems to IBM. Early knowledge about potential problems enables IBM to deliver proactive service that may result in higher system availability and performance. In addition, information collected through the Service Agent is made available to IBM service support representatives when they help answer your questions or diagnose problems. Installation and use of IBM Electronic Service Agent for problem reporting enables IBM to provide better support and service for your IBM server.

To learn how Electronic Services can work for you, visit

<http://www.ibm.com/support/electronic>

Terms and conditions

To obtain copies of the IBM Statement of Limited Warranty, contact your reseller or IBM.

Warranty period

- Three years
- Optional features - One year

An IBM part or feature installed during the initial installation of an IBM machine is subject to a full warranty effective on the date of installation of the machine. An IBM part or feature that replaces a previously installed part or feature assumes the remainder of the warranty period for the replaced part or feature. An IBM part or feature added to a machine without replacing a previously installed part or feature is subject to a full warranty effective on its date of installation. Unless specified otherwise, the warranty period, type of warranty service, and service level of a part or feature are the same as those for the machine in which it is installed.

The following have been designated as consumables or supply items and are, therefore, not covered by this warranty:

- RAID batteries

Warranty service

If required, IBM provides repair or exchange service, depending on the type of warranty service specified below for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. Certain machines contain remote support capabilities for direct problem reporting, remote problem determination, and resolution with IBM. You must follow the problem determination and resolution procedures that IBM specifies. Following problem determination, if IBM determines On-site Service is required, scheduling of service will depend upon the time of your call, machine technology and redundancy, and availability of parts. Service levels are response-time objectives and are not guaranteed. The specified level of warranty service may not be available in all worldwide locations. Additional charges may apply outside IBM's normal service area. Contact your local IBM representative or your reseller for country- and location-specific information.

The type of service is Customer Replaceable Unit (for example, keyboard, mouse, speaker, memory, or hard disk drive) Service and On-site Service.

Customer Replaceable Unit (CRU) Service

IBM provides a replacement CRU to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request. A CRU is designated as being either a Tier 1 (mandatory) or a Tier 2 (optional) CRU. Installation of Tier 1 CRUs, as specified in this announcement, is your responsibility. If IBM installs a Tier 1 CRU at your request, you will be charged for the installation. You may install a Tier 2 CRU yourself or request IBM to install it, at no additional charge, under the type of warranty service designated for your machine.

Based upon availability, a CRU will be shipped for next business day (NBD) delivery. IBM specifies in the materials shipped with a replacement CRU whether a defective CRU must be returned to IBM. When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

The following parts or features have been designated as Tier 1 CRUs:

- Air baffles
- Blank filler
- CMOS batteries
- Cable-management arm
- Hard disk drives
- Hot-swap fan
- Hot-swap AC power supply
- Lift handle kit
- Memory DIMM
- Optical drive
- PCI adapter
- Power cord
- Service label
- System label
- Top cover
- Fan bracket
- Hypervisor™ USB key
- PCI riser
- RAID card without battery
- Tape drive
- Ethernet daughter card

On-site Service

At IBM's discretion you will receive CRU service or IBM or your reseller will repair the failing machine at your location and verify its operation. If required, On-site Repair is provided, 9 hours per day, Monday through Friday excluding holidays, NBD response. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well lit, and suitable for the purpose. On-site Service is not available in all countries, and some countries have kilometer or mileage limitations from an IBM service center. In those locations where On-site Service is not available, the normal in-country service delivery is used.

International Warranty Service

International Warranty Service (IWS) is available in selected countries or regions.

The warranty service type and the service level provided in the servicing country may be different from that provided in the country in which the machine was purchased.

Under IWS, warranty service will be provided with the prevailing warranty service type and service level available for the IWS-eligible machine type in the servicing country, and the warranty period observed will be that of the country in which the machine was purchased.

To determine the eligibility of your machine and to view a list of countries where service is available, visit

<http://www-304.ibm.com/jct01004c/systems/support/supportsite.wss/warrantyform?brandind=5000008>

For more information on IWS, refer to Services Announcement 601-034, dated September 25, 2001.

Licensing

Programs included with this product are licensed under the terms and conditions of the License Agreements that are shipped with the system.

Warranty service upgrades

IBM hourly service rate classification

Two

Field-installable features

Yes

Model conversions

No

Machine installation

Customer setup. Customers are responsible for installation according to the instructions IBM provides with the machine.

Licensed Machine Code

IBM Machine Code is licensed for use by a customer on the IBM machine for which it was provided by IBM under the terms and conditions of the IBM License Agreement for Machine Code, to enable the machine to function in accordance with its specifications, and only for the capacity authorized by IBM and acquired by the customer. You can obtain the agreement by contacting your IBM representative or visiting

http://www-304.ibm.com/systems/support/machine_warranties/machine_code.html

IBM may release changes to the Machine Code. IBM plans to make the Machine Code changes available for download from the IBM System x technical support website:

<http://www-304.ibm.com/systems/support/>

If the machine does not function as warranted and your problem can be resolved through your application of downloadable Machine Code, you are responsible for downloading and installing these designated Machine Code changes as IBM specifies. If you would prefer, you may request IBM to install downloadable Machine Code changes; however, you may be charged for that service.

Pricing

For all local charges, contact your IBM representative.

ServicePac® service upgrades

The announced products are also eligible for ServicePac warranty upgrades. ServicePacs provide a higher level of service than that provided under the base IBM Machine Warranty.

ServicePacs can be purchased from your IBM Business Partner and are specific to the machines/products listed.

Machine type 7945

ServicePac offering	PC no		Ordering part number
3yr On-site Repair 9hr x 5 days 4hr Resp Target	PC1074	e-ServicePac	- 65Y5220 (2)
3yr On-site Repair 24hr x 7 days 4hr Resp Target	PC1075	e-ServicePac	- 65Y5221 (2)
3yr On-site Repair 24hr x 7 days 6hr Committed Service	PC506	e-ServicePac	- 41w9360(4)
3yr On-site Repair 24hr x 7 days 6hr Committed Service	PC935	e-ServicePac	- 54Y4501 (UK only)
3yr On-site Repair 24hr x 7 days 6hr Committed Service	PC1097	e-ServicePac	- 68Y5030 (Italy Only)
3yr On-site Repair 24hr x 7 days 6hr Committed Service	PC1121	e-ServicePac	- 68Y5151 (12)
3yr On-site Repair 24hr x 7 days 8hr Committed Service	PC529	e-ServicePac	- 41w9680 (5)
3yr On-site Repair 24hr x 7 days 8hr Committed Service	PC1108	e-ServicePac	- 68Y4933 (9)
3yr On-site Repair 24hr x 7 days 24hr Committed Service	PC926	e-ServicePac	- 40Y5878 (6)
3yr On-site Repair 24hr x 7 days 24hr Committed Service	PC517	e-ServicePac	- 41w9371 (7)
4yr On-site Repair 9hr x 5 days 4hr Resp Target	PC1076	e-ServicePac	- 65Y5220 (2)
4yr On-site Repair 9hr x 5 days 4hr Resp Target	PC1076	e-ServicePac	- 65Y5222 (2)
4yr On-site Repair 24hr x 7 days 4hr Resp Target	PC1077	e-ServicePac	- 65Y5223 (2)
5yr On-site Repair 9hr x 5 days 4hr Resp Target	PC1078	e-ServicePac	- 65Y5224 (2)

5yr On-site Repair PC1079 e-ServicePac - 65Y5225 (2)
24hr x 7 days 4hr Resp Target

3yr On-site Repair PC1024 e-ServicePac - 65Y0991
9hr x 5 days NBD Comm Parts (Russia only)

Announcement countries for ServicePacs

Announcement is restricted to the following countries:

e-ServicePac

Austria	Belgium	Bulgaria	Croatia	Czech Rep
Denmark	Egypt	Estonia(8)	Finland	France (1)
Germany	Greece	Hungary	Ireland	Israel
Italy	Latvia(8)	Lithuania(8)	Luxembourg	Morocco(9)
Netherlands	Norway	Pakistan	Poland	Portugal
Romania	Russia(2)	Serbia	Slovakia	Slovenia
South Africa	Spain	Sweden	Switzerland	Tunisia(10)
Turkey	Ukraine	United Kingdom(3)		

(1) Except overseas Territories

(2) Except Russia

(3) UK mainland only

(4) Austria, Germany, South Africa and Turkey Only

(5) Czech Republic, Hungary, Poland, Slovakia, Slovenia, Serbia, Morocco, Tunisia, Switzerland, Romania, Russia, Bulgaria and Croatia only

(6) Austria, Germany, Belgium, Netherlands, Luxembourg, South Africa and Switzerland only

(7) Czech Republic, Hungary, Poland, Slovakia, Slovenia, Serbia, Morocco, Tunisia, Turkey, Romania, Russia, Bulgaria and Croatia only

(8) Order and registration via Finland

(9) Restricted to 50km of Casablanca/Rabat

(10) Restricted to 50km of Tunis

(11) Denmark, Sweden, Finland and Norway only

(12) France, Belgium, Netherlands and Luxembourg only

Maintenance

The products in this document are also covered by Maintenance Agreements and ServiceSuite™ contracts.

IBM Global Financing

IBM Global Financing offers competitive financing to credit-qualified customers to assist them in acquiring IT solutions. Offerings include financing for IT acquisition, including hardware, software, and services, from both IBM and other manufacturers or vendors. Offerings (for all customer segments: small, medium, and large enterprise), rates, terms, and availability can vary by country. Contact your local IBM Global Financing organization or visit

<http://www.ibm.com/financing>

IBM Global Financing offerings are provided through IBM Credit LLC in the United States, and other IBM subsidiaries and divisions worldwide to qualified commercial and government customers. Rates are based on a customer's credit rating, financing terms, offering type, equipment type, and options, and may vary by country. Other restrictions may apply. Rates and offerings are subject to change, extension, or withdrawal without notice.

Financing solutions from IBM Global Financing can help you stretch your budget and affordably acquire the new product. But beyond the initial acquisition, our end-to-end approach to IT management can also help keep your technologies current, reduce costs, minimize risk, and preserve your ability to make flexible equipment decisions throughout the entire technology life cycle.

Announcement countries

All European, Middle Eastern, and African countries.

Trademarks

IBM Systems Director Active Energy Manager, ServerGuide, Chipkill, Electronic Service Agent, Hypervisor and ServiceSuite are trademarks of IBM Corporation in the United States, other countries, or both.

IBM, X-Architecture, Predictive Failure Analysis, Wake on LAN, System x, Tivoli, NetView, BladeCenter, ServerProven, xSeries, Netfinity and ServicePac are registered trademarks of IBM Corporation in the United States, other countries, or both.

Intel and Xeon are registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States, other countries, or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product, and service names may be trademarks or service marks of others.

Terms of use

IBM products and services which are announced and available in your country can be ordered under the applicable standard agreements, terms, conditions, and prices in effect at the time. IBM reserves the right to modify or withdraw this announcement at any time without notice. This announcement is provided for your information only. Reference to other products in this announcement does not necessarily imply those products are announced, or intend to be announced, in your country. Additional terms of use are located at

<http://www.ibm.com/legal/us/en/>

For the most current information regarding IBM products, consult your IBM representative or reseller, or visit the IBM worldwide contacts page

<http://www.ibm.com/planetwide/>