

# QLogic 8200 Virtual Fabric Adapter Family for IBM System x

## IBM Redbooks Product Guide

The QLogic 8200 Virtual Fabric Adapter Family for IBM System x consists of 10 Gigabit Ethernet adapters available in either a standard PCIe adapter form factor or a mezzanine form factor. Both adapters are high-performance Converged Network Adapters (CNAs) based on the new QLogic 8200 design. The adapters offer upgrades to full hardware offload for Fibre Channel over Ethernet (FCoE) and iSCSI processing. The adapters connect to SFP+ Multimode Fiber SR optical modules and direct-attach copper (DAC) cables.

The QLogic 8200 Dual Port 10GbE SFP+ VFA is shown in the following figure.



Figure 1. QLogic 8200 Dual Port 10GbE SFP+ VFA for IBM System x

### Did you know

With the IBM Features on Demand (FoD) entitlement upgrade, the QLogic 8200 adapters support full hardware offload for FCoE and iSCSI protocol processing. This feature frees up the server's CPU to perform other tasks. Consequently, the server's applications can run faster and virtualized servers can support more virtual machines.

The QLogic Dual Port 10GbE SFP+ Embedded Virtual Fabric Adapter (VFA) is designed specifically to fit in to a dedicated slot in servers such as the IBM® System x3650 M4 and x3550 M4. This card design allows you to use the server's standard PCIe slots for other technologies.

## Part number information

The following table shows the ordering part numbers and feature codes for these adapters.

Table 1. Ordering part numbers and feature codes

Description	Part number	Feature code
Standard PCIe adapter		
QLogic 8200 Dual Port 10GbE SFP+ VFA for IBM System x	90Y4600	A3MR
QLogic 8200 VFA FCoE/iSCSI License for IBM System x (Features on Demand)	00Y5624	A3MT
Embedded PCIe adapter		
QLogic Dual Port 10GbE SFP+ Embedded VFA for IBM System x	90Y6454	A22H
QLogic Embedded VFA FCoE/iSCSI License for IBM System x (Features on Demand)	90Y5179	A2TF

The part numbers for the adapters (90Y4600 and 90Y6454) includes the following items:

- One QLogic adapter
- 3U bracket attached with 2U bracket included in the box (90Y4600 only)
- Support CD
- Safety flyer

The QLogic Dual Port 10GbE SFP+ Embedded VFA is shown in the following figure.



Figure 2. QLogic Dual Port 10GbE SFP+ Embedded Virtual Fabric Adapter

Transceivers are not included with the adapter. The adapters support the SFP+ SR transceivers and direct-attach copper (DAC) cables listed in the following table.

Table 2. Supported transceivers and DAC cables

Description	Option part number	Feature code
Optical Transceivers		
QLogic 10Gb SFP+ SR Optical Transceiver	49Y4218	0064
Brocade 10Gb SFP+ SR Optical Transceiver	49Y4216	0069
IBM SFP+ SR Transceiver	46C3447	5053
Active Direct-attach copper (DAC) cables		
1m IBM Active DAC SFP+ Cable	95Y0323	A25A
3m IBM Active DAC SFP+ Cable	95Y0326	A25B
5m IBM Active DAC SFP+ Cable	95Y0329	A25C
Passive Direct-attach copper (DAC) cables		
.5m IBM Passive DAC SFP+ Cable	00D6288	A3RG
0.5m IBM Passive DAC SFP+ Cable	00D6288	A3RG
1m IBM Passive DAC SFP+ Cable	90Y9427	A1PH
3m IBM Passive DAC SFP+ Cable	90Y9430	A1PJ
5m IBM Passive DAC SFP+ Cable	90Y9433	A1PK
7m IBM Passive DAC SFP+ Cable	00D6151	A3RH

The following figure shows the component side of the QLogic Dual Port 10GbE SFP+ Embedded VFA.




Figure 3. QLogic Dual Port 10GbE SFP+ Embedded VFA

## Features

The QLogic 8200 VFA family is based on the QLogic second generation of Converged Network Controllers, supporting simultaneous LAN (TCP/IP) and SAN (FCoE and iSCSI) traffic at line-rate, 10 Gbps Ethernet speed. This convergence of networking traffic lowers data center costs by eliminating the need for separate LAN and SAN infrastructure. Data centers now need fewer adapters, cables, and switches, which also means reduced power and cooling costs. In addition, these controllers are fully compatible with existing Fibre Channel and iSCSI storage, providing investment protection for existing infrastructure.

The QLogic 8200 VFA family adapters have the following features:

- 10 Gbps per-port maximum throughput for high bandwidth storage (SAN) and networking (LAN) traffic.
- Based on the QLogic 8200 ASIC.
- PCI Express 2.0 x8 host interface.
- Operate at full 10 Gbps line rate on both ports.
- Support for SFP+ transceivers and DAC cables.
- Two form factors:
  - Standard PCIe low-profile form factor adapter fits most M4 systems.
  - Mezzanine form-factor card installed in a dedicated slot on the system board of supported servers.
- Support for Switch Independent vNIC mode, also known as NIC Partitioning or NPAR, where each physical port appears to the server as four virtual NICs. Bandwidth for each vNIC can be configured from 100 Mbps to 10 Gbps. This vNIC mode extends the existing VLANs to the virtual NIC interfaces. It uses IEEE 802.1Q VLAN tags to separate data traffic; the VLAN tags are added to the packet by the applications or drivers rather than by the switch.
- Support for full FCoE and iSCSI hardware offload through the Features on Demand (FoD) license upgrade. This support enables flexibility and investment protection by letting you buy the FCoE or iSCSI license when you need it. FCoE and iSCSI can also be enabled with 4 of the vNIC ports (2 FCoE, 2 iSCSI) if vNIC is also enabled.
- Full support for TCP/IP and Ethernet performance enhancements, such as Priority-Based Flow Control (802.1Qbb), jumbo frames, checksum offloads, and segmentation offloads.
- Support for IPv4 and IPv6.
- Support for Wake on LAN.
- Port 1 can be configured to be a shared management port to remotely connect to the IMM2 management controller.

**Note:** The adapter only supports connectivity to a 10 Gb Ethernet switch. 1 Gb Ethernet connectivity is not supported.

Check the IBM System Storage Interoperation Center (SSIC) for full listing of IBM supported FCoE & iSCSI configurations:

<http://ibm.com/systems/support/storage/ssic/interoperability.wss>

## Specifications

The QLogic 8200 VFA family adapters have the following specifications:

### Ethernet specifications

- Throughput: 10 Gbps full-duplex line rate per-port
- Ethernet frame: 1500 byte or 9600 byte (jumbo frame)
- Stateless offload:
  - IP, TCP, and UDP checksum offloads
  - Large and giant send offload (LSO and GSO)
  - Large receive offload (LRO)
  - Receive side scaling (RSS)
  - Header-data split
  - Interrupt coalescing
  - VMware NetQueue and Microsoft VMQ
- Wake on LAN
- Enhanced Ethernet
  - Priority-Based Flow Control (802.1Qbb)
  - Enhanced Transmission Selection (802.1Qaz)
  - DCBX Protocol (802.1Qaz)
- Compliance
  - IEEE: 802.3ae (10 Gb Ethernet)
  - 802.3ap (10GBASE-KR)
  - 802.1q (VLAN)
  - 802.3ad (Link Aggregation)
  - 802.1p (Priority Encoding)
  - 802.3x (Flow Control)
  - IPv4 (RFQ 791)
  - IPv6 (RFC 2460)

### FCoE specifications

- Logins: Support for 2,048 concurrent logins and 2,048 active exchanges
- Port virtualization: N\_Port ID virtualization (NPIV)
- Compliance:
  - SCSI-3 Fibre Channel Protocol (SCSI-FCP)
  - Fibre Channel Tape (FC-TAPE) Profile
  - SCSI Fibre Channel Protocol-2 (FCP-2)
  - Second Generation FC Generic Services (FC-GS-2)
  - Third Generation FC Generic Services (FC-GS-3)
  - FCoE and FIP (FC-BB-5)

### iSCSI Specifications

- Compliance
  - RFC 3347 (iSCSI Requirements and Design Considerations)
  - CHAP
  - iSNS
  - SLP

## Supported servers

The adapter is supported in the System x servers listed in the following table.

Table 3. Supported System x servers (Part 1)

Product description	Part number												
		x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383)	x3530 M4 (7160)	x3550 M4 (7914)	x3630 M4 (7158)	x3650 M4 (7915)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912)
QLogic 8200 Dual Port 10GbE SFP+ VFA	90Y4600	N	Y	Y	N	Y	Y	Y	Y	N	Y	N	Y
QLogic 8200 VFA FCoE/iSCSI License (FoD)	00Y5624	N	N	Y	N	Y	Y	Y	Y	N	Y	N	Y
QLogic Dual Port 10GbE SFP+ Embedded VFA	90Y6454	N	N	N	N	N	Y†	N	Y†	N	N	N	Y
QLogic Embedded VFA FCoE/iSCSI License (FoD)	90Y5179	N	N	N	N	N	Y	N	Y	N	N	N	Y

† The Embedded VFA, 90Y6454, requires both processors be installed in the server to ensure sufficient air flow. The second processor includes additional system fans.

Table 3. Supported System x servers (Part 2)

Product description	Part number												
		x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)		
QLogic 8200 Dual Port 10GbE SFP+ VFA	90Y4600	N	N	N	N	N	N	N	N	N	N	N	N
QLogic 8200 VFA FCoE/iSCSI License (FoD)	00Y5624	N	N	N	N	N	N	N	N	N	N	N	N
QLogic Dual Port 10GbE SFP+ Embedded VFA	90Y6454	N	N	N	N	N	N	N	N	N	N	N	N
QLogic Embedded VFA FCoE/iSCSI License (FoD)	90Y5179	N	N	N	N	N	N	N	N	N	N	N	N

For the latest information about the System x servers that support this adapter, see the IBM ServerProven® website at <http://ibm.com/servers/eserver/serverproven/compat/us/>

The following figure shows where the QLogic Dual Port 10GbE SFP+ Embedded VFA is installed in the x3650 M4 server. Its location and connection does not consume any of the available standard PCIe slots.




Figure 3. Rear of the IBM System x3650 M4



## Popular configurations

This section illustrates how the QLogic Dual Port 10GbE SFP+ Embedded VFA can be used in 10 Gb Ethernet configurations.

The following figure shows the adapter installed in the x3650 M4 and connected to a pair of IBM RackSwitch G8124E top-of-rack switches.




Figure 4. 10 Gb Ethernet solution

The parts used are listed in the following table. We provide two cabling options: a direct-attach copper (DAC) cable option and a fiber optic cable option.

Table 4. Components used when connecting the QLogic adapter to Ethernet switches

Part number/ machine type	Description	Quantity
7915	IBM System x3650 M4 or other supported server	1
90Y6454	QLogic Dual Port 10GbE SFP+ Embedded VFA	1
7309BF7	IBM RackSwitch G8124E	2
<b>Direct-attach copper (DAC) cable connectivity</b>		
95Y0323	1 m IBM Active DAC SFP+ Cable	2
<b>Fibre optic cable connectivity</b>		
49Y4218	QLogic 10Gb SFP+ SR Optical Transceiver	2
46C3447	IBM SFP+ SR Transceiver (for the G8124E)	2
88Y6851	1 m LC-LC Fiber Cable (networking) - Optical	2



## Supported operating systems

The adapters supports the following operating systems:

- Microsoft Windows HPC Server 2008
- Microsoft Windows Server 2008 R2
- Microsoft Windows Server 2008, Datacenter x64 Edition
- Microsoft Windows Server 2008, Datacenter x86 Edition
- Microsoft Windows Server 2008, Enterprise x64 Edition
- Microsoft Windows Server 2008, Enterprise x86 Edition
- Microsoft Windows Server 2008, Standard x64 Edition
- Microsoft Windows Server 2008, Standard x86 Edition
- Microsoft Windows Server 2008, Web x64 Edition
- Microsoft Windows Server 2008, Web x86 Edition
- Microsoft Windows Server 2012
- Windows Small Business Server 2008 Premium Edition
- Windows Small Business Server 2008 Standard Edition
- Red Hat Enterprise Linux 5 Server with Xen x64 Edition
- Red Hat Enterprise Linux 5 Server x64 Edition
- Red Hat Enterprise Linux 6 Server Edition
- Red Hat Enterprise Linux 6 Server x64 Edition
- SUSE Linux Enterprise Server 10 for AMD64/EM64T
- SUSE Linux Enterprise Server 11 for AMD64/EM64T
- SUSE Linux Enterprise Server 11 for x86
- SUSE Linux Enterprise Server 11 with Xen for AMD64/EM64T
- VMware ESX 4.1
- VMware ESXi 4.1
- VMware vSphere 5
- VMware vSphere 5.1

For the latest information about the specific versions and service packs supported, see the IBM ServerProven website at:

<http://ibm.com/servers/eserver/serverproven/compat/us/>

## Warranty

The adapters carry a 1-year, customer-replaceable unit (CRU) limited warranty. When installed in a supported IBM server, these adapters assume your system's base warranty and any IBM ServicePac® upgrade.

## Physical specifications

The QLogic 8200 Dual Port 10GbE SFP+ VFA for IBM System x has the following physical specifications:

Dimensions and weight (approximate):

- Height: 167 mm (6.60 in)
- Width: 69 mm (2.71 in)
- Depth: 17 mm (0.69 in)
- Weight: 95 g (0.21 lb)

Shipping dimensions and weight (approximate):

- Height: 189 mm (7.51 in)
- Width: 90 mm (3.54 in)
- Depth: 38 mm (1.50 in)
- Weight: 450 g (0.99 lb)

The QLogic Dual Port 10GbE SFP+ Embedded VFA has the following physical specifications:

Dimensions (approximate):

- Height: 60 mm (2.4 in)
- Width: 160 mm (6.3 in)
- Depth: 17 mm (0.7 in)

## Operating environment

The adapter is supported in this environment:

- Temperature:
  - Operating: 0° - 55°C (32° - 113°F) at 0 - 914 m (0 - 3000 ft)
  - Storage: -43° - 73°C (-40° - 163°F) at 0 - 914 m (0 - 3000 ft)
- Relative humidity: 5% - 93% (non-condensing)

## Agency approvals

The adapters have the following agency approvals:

- Safety: US, Canada, Europe
- EMI
- EMC
- EN55022
- EN55024
- EN60950 / CE
- EN 61000-3-2
- EN 61000-3-3
- IEC 950 CB Scheme
- FCC Part 15 Class A
- UL 1950
- CSA C22.2 950-95
- VCCI
- NZ AS3548 / C-tick
- RRL for MIC (KCC)
- BSMI
- UL 94-/V

## Related publications

For more information, refer to these documents:

- Product web page  
<http://ibm.com/systems/x/options/networking/adapters.html>
- Announcement letter for the QLogic 8200 Dual Port 10GbE SFP+ VFA  
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS112-219>
- Announcement letter for the QLogic Dual Port 10GbE SFP+ Embedded VFA  
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS112-144>
- *IBM System x Configuration and Options Guide*  
<http://www.ibm.com/support/docview.wss?uid=psg1SCOD-3ZVQ5W>
- IBM System Storage Interoperation Center (SSIC)  
<http://ibm.com/systems/support/storage/ssic/interoperability.wss>
- *IBM System x Networking Interoperability Guide*  
<http://ibm.com/common/ssi/cgi-bin/ssialias?htmlfid=XSO03137USEN>

# Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing, IBM Corporation, North Castle Drive, Armonk, NY 10504-1785 U.S.A.*

**The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:** INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you. This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk. IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products. This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

## COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs.

**© Copyright International Business Machines Corporation 2012. All rights reserved.**

Note to U.S. Government Users Restricted Rights -- Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

This document was created or updated on April 8, 2013.

Send us your comments in one of the following ways:

- Use the online **Contact us** review form found at:  
[ibm.com/redbooks](http://ibm.com/redbooks)
- Send your comments in an e-mail to:  
[redbook@us.ibm.com](mailto:redbook@us.ibm.com)
- Mail your comments to:  
IBM Corporation, International Technical Support Organization  
Dept. HYTD Mail Station P099  
2455 South Road  
Poughkeepsie, NY 12601-5400 U.S.A.

This document is available online at <http://www.ibm.com/redbooks/abstracts/tips0874.html> .

## Trademarks

IBM, the IBM logo, and [ibm.com](http://ibm.com) are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. These and other IBM trademarked terms are marked on their first occurrence in this information with the appropriate symbol (® or ™), indicating US registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at <http://www.ibm.com/legal/copytrade.shtml>.

The following terms are trademarks of the International Business Machines Corporation in the United States, other countries, or both:

IBM®  
Redbooks (logo)®  
ServerProven®  
System x®

The following terms are trademarks of other companies:

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.